

26610



Chemical product data sheet

address STAEDTLER Mars GmbH & Co. KG
Moosaeckerstr. 3
90427 Nuernberg

phone +49 911 93 65 - 888
fax +49 911 93 65 - 769
internet www.staedtler.de
e-mail service@staedtler.de

Article description

STAEDTLER Lumocolor permanent universal pens 313, 314, 317, 318 - permanent pen 310 CDS

Constituents

Inks: Alcohol mix- e.g. propanol, ethyl alcohol
Dyestuffs – colouring agents containing toxic heavy metals are not used
Resin-based binding agent and additives

Holder: Plastics:

Barrel	PP
Cap	PP
Sealing (Cap)	PE
Refill station 487 17:	PP

Packaging: STAEDTLER Box: PP

PP: polypropylene, PE: polyethylene

Toxicology

Not harmful if used in the proper manner.
STAEDTLER products are subject to comprehensive quality inspections.
REACH SAFETY DATA SHEETS for the refill station 487 17 can be provided to commercial buyers.

Conformity

STAEDTLER Lumocolor permanent pens 310, 313, 314, 317, 318 meet the standards:

ISO 11540 'Caps for writing and marking instruments intended for use by children up to 14 years of age – Safety requirements'.
Ventilated caps reduce the danger of asphyxiation for children up to the age of 14 should caps be swallowed accidentally.

ISO 554 Standard atmospheres for conditioning and/or testing – Specifications.
This standard contains the test parameters for the dry safe properties.

ASTM D-4236 Tested for the USA by toxicologists from the Art & Creative Material Institute, Inc. (ACMI)
For 313, 314, 317, 318 The above mentioned products conform to the US standard ASTM D-4236.

Usage notes

Dry safe: Can be left uncapped for days without drying up.

Marking: No ink migration when used on STAEDTLER overhead film.
Please test on other surfaces first.
Not suitable for use on coated surfaces whose top layer can be easily removed.

Airplane-safe: Automatic pressure equalisation prevents the pens from leakage during flight.

Refill 487 17: Available for the colours red, blue, green and black.

We reserve the right to revise product compounds for development and improvement reasons.
The suitability of our products for applications intended by the user has to be verified at the user's own risk.