

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

AEROSPRAY fixative for pastels / water-colours

Article No.

Version

4 (08.12.16)

Issue date:

Page

08.12.16

1 / 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name 50 402 - AEROSPRAY fixative for pastels
50 403 - AEROSPRAY fixative for water-colours

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use

Products for creation of art.

Uses advised against

1.3 Details of the supplier of the safety data sheet

H. Schmincke & Co. GmbH & Co. KG
Otto-Hahn-Str. 2
D - 40699 Erkrath
Tel. +49 (0) 211-2509-0
Fax. +49 (0) 211-2509-497
info@schmincke.de
www.schmincke.de

Dept. responsible for information

Schmincke-lab:
mo-th 8.00-16.30, fr 8.00-13.30
Tel. +49 (0) 211-2509-474
labor@schmincke.de

1.4 Emergency telephone number

**Emergency
Information
Phone #**

**Emergencycall Berlin
(24h - counseling in german and english)
+49 (0) 30-30686790**

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Eye Irrit. 2; H319 Causes serious eye irritation.
Flam. Aerosol 1; H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
STOT SE 3; H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling (CLP)



Signal word

Danger

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Safety precautions

P102 Keep out of reach of children.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

AEROSPRAY fixative for pastels / water-colours

Article No.		Issue date:	08.12.16
Version	4 (08.12.16)	Page	2 / 9

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe spray.
P271 Use only outdoors or in a well-ventilated area.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

2.3 Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 3: Composition / information on ingredients

3.1 Substances

Chemical characterisation

Polyvinyl resin
Alcohol
propellant (propane / butane)

CAS-Number
EINECS / ELINCS / NLP
EU index number
Customs tariff number
REACH registration No.
RTECS-no.
Hazchem-Code
CI-Number

3.2 Mixtures

Substance 1

propan-2-ol: 30 - 50 %
CAS: 67-63-0
REACH: 01-2119457558-25
Eye Irrit. 2; H319 / Flam. Liq. 2; H225 / STOT SE 3;
H336

Substance 2

ethanol: 10 - 25 %
CAS: 64-17-5
Eye Irrit. 2; H319 / Flam. Liq. 2; H225

Substance 3

4-hydroxy-4-methylpentan-2-one: 1 - 10 %
CAS: 123-42-2
REACH: 01-2119473975-21-XXXX
Eye Irrit. 2; H319 / Flam. Liq. 3; H226 / STOT SE 3;
H335

Substance 4

propane / butane: < 30 %
CAS: 74-98-6 / 106-97-8
REACH: 01-2119471330-49 / 01-2119474691-32
Compr. Gas; H280 / Flam. Gas 1; H220

Additional information

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of inhalation

Move victim to fresh air, put at rest and loosen restrictive clothing. Seek medical attention if problems persist.

In case of skin contact

Thoroughly wash skin with soap and water. Seek medical attention if irritation persists.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

AEROSPRAY fixative for pastels / water-colours

Article No.		Issue date:	08.12.16
Version	4 (08.12.16)	Page	3 / 9

After eye contact

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After swallowing

Call a POISON CENTER/doctor/. if you feel unwell. Caution if victim vomits: Risk of aspiration!

4.2 Most important symptoms and effects, both acute and delayed

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

extinguishing powder carbon dioxide Water fog

Extinguishing media which must not be used for safety reasons

5.2 Special hazards arising from the substance or mixture

5.3 Advice for firefighters

Special protective equipment for firefighters

Use appropriate respiratory protection.

Additional information

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

refer to section 8

6.2 environmental precautions

Do not allow to enter into surface water or drains.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up

Absorb leftover product with non-flammable liquid-binding material (e.g. earth, sand, vermiculite or ground sand stone) and place in closed containers for disposal.

Additional information

6.4 Reference to other sections

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling

Provide good ventilation and/or an exhaust system in the work area. In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Precautions against fire and explosion

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers

Store in a well-ventilated place. Keep container tightly closed.

Hints on joint storage

Storage class

Further details

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

67-63-0 propan-2-ol

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

AEROSPRAY fixative for pastels / water-colours

Article No.
Version

4 (08.12.16)

Issue date:
Page

08.12.16
4 / 9

DEU	WEL	200,000	mL/m ³	-
DEU	WEL	500,000	mg/m ³	2(II); DFG; Y

64-17-5 ethanol

DEU	WEL	500,000	mL/m ³	-
DEU	WEL	960,000	mg/m ³	2(II); DGF; Y
USA	PEL (US)	1.000,000	ppm	8h (long term)
USA	PEL (US)	1.900,000	mg/m ³	8h (long term)

123-42-2 4-hydroxy-4-methylpentan-2-one

DEU	WEL	20,000	mL/m ³	-
DEU	WEL	96,000	mg/m ³	2(I); DGF; H
USA	PEL (US)	50,000	ppm	(8h long term)
USA	PEL (US)	240,000	mg/m ³	(8h long term)

74-98-6 / 106-9 propane / butane

DEU	WEL	1.000,000	mL/m ³	-
DEU	WEL	1.800,000	mg/m ³	4(II); DFG

8.2 Exposure controls

Occupational exposure controls

Respiratory protection

Respiratory protection must be worn whenever the WEL levels have been exceeded.

Combination filtering device (EN 14387) Use filter type A (= against vapours of organic substances)

Hand protection

Qualified materials: Butyl caoutchouc (butyl rubber)

Layer thickness > 0,5 mm

Breakthrough time > 480 min

Butoflex 650 - MAPA GmbH, Industriestraße 21- 25, D-27404 Zeven, Internet: www.mapa-pro.de

All information was derived in accordance with EU directive 89/686/EEG and the resultant EN 374 in cooperation with MAPA GmbH. This recommendation applies exclusively to the product and use named in Section 1. In the event of commingling or deviating conditions, contact the suppliers of CE-approved gloves.

Eye protection

Avoid contact with eyes.

Body protection

Wash contaminated clothing prior to re-use.

General protection and hygiene measures

Handle in accordance with good industrial hygiene and safety practice.

SECTION 9: Physical and chemical properties

9.1 information on basic physical and chemical properties

Form Aerosol
Colour colourless
Odour aromatic

	min	max
Initial boiling point and boiling range		
Melting point/freezing point		
Flash point/flash point range	-60 °C	-60 °C
Flammability		
Ignition temperature		
Auto-ignition temperature		
Explosion limits		
Refraction index		

Partition coefficient: n-octanol/water

Danger of explosion

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

AEROSPRAY fixative for pastels / water-colours

Article No. Issue date: 08.12.16
Version 4 (08.12.16) Page 5 / 9

Vapour pressure 3500 hPa
Density 0,6 -
0,7 g/ml
PH value

Viscosity dynamic of
Viscosity dynamic up to

Viscosity kinematic of
Viscosity kinematic up to

9.2 Other information

SECTION 10: Stability and reactivity

10.1 Reactivity

10.2 Chemical stability

10.3 Possibility of hazardous reactions

10.4 Conditions to avoid

Protect from heat and direct sunlight.

10.5 Incompatible materials

Oxidising agent

10.6 Hazardous decomposition products

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity
In case of inhalation
After swallowing
In case of skin contact
After eye contact

Practical experience

General remarks

Toxicological tests

67-63-0	propan-2-ol						
	oral	LD50	Rat		5050,000	mg/kg	-
64-17-5	ethanol						
	oral	LD50	Rat		5000,000	mg/kg	-
	inhalative	LC50	Rat		1800,000	mg/l	4h
	dermal	LD50	Rabbit		10000,000	mg/kg	-
123-42-2	4-hydroxy-4-methylpentan-2-one						
	oral	LD50	Rat		4000,000	mg/kg	-
	dermal	LD50	Rabbit		13500,000	mg/kg	-

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity
Water Hazard Class

1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

AEROSPRAY fixative for pastels / water-colours

Article No. Issue date: 08.12.16
Version 4 (08.12.16) Page 6 / 9

WGK catalog number
General information

12.2 Persistence and degradability

Further details
Oxygen demand

12.3 Bioaccumulative potential

Bioconcentration factor (BCF)
Partition coefficient: n-octanol/water

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other adverse effects

General information

Ecotoxicological effects

67-63-0 propan-2-ol

LC50	fish		1000,000	mg/l	(96h)
------	------	--	----------	------	-------

64-17-5 ethanol

LC50	fish		8150,000	mg/l	48h
------	------	--	----------	------	-----

EC50	Daphnia magna		14221,000	mg/l	48h
------	---------------	--	-----------	------	-----

123-42-2 4-hydroxy-4-methylpentan-2-one

LC50	fish		420,000	mg/l	(96 h)
------	------	--	---------	------	--------

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste key number 160504 160504* Gases in pressure containers (including halons) containing dangerous substances.
Recommendation

Contaminated packaging

Waste key number
Recommendation Completely emptied packages can be recycled.

Additional information

SECTION 14: Transport information

14.1 UN number

1950

14.2 UN proper shipping name

ADR, ADN AEROSOLS, flammable
IMDG, IATA AEROSOLS, flammable

14.3 Transport hazard class(es)

ADR, ADN 2
IMDG 2.1
IATA 2.1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

AEROSPRAY fixative for pastels / water-colours

Article No.		Issue date:	08.12.16
Version	4 (08.12.16)	Page	7 / 9

14.4 Packing group

-

14.5 Environmental hazards

Marine Pollutant - IMDG	No
Marine Pollutant - ADN	-

14.6 Special precautions for user

Land transport

Code: ADR/RID	5F
Kemmler-number	-
Hazard label ADR	2.1
Limited quantities	1L
Contaminated packaging: Instructions	P207 - LP02
Contaminated packaging: Special provisions	PP87 - RR6 - L2
Special provisions for packing together	MP9
Portable tanks: Instructions	-
Portable tanks: Special provisions	-
Tank coding	-
Tunnel restriction	D
Remarks	
EQ	E0
Special provisions	190 - 327 - 344 - 625

Inland waterway craft

Hazard label	
Limited quantities	
Transport permitted	
Equipment necessary	
Ventilation	
Remarks	
EQ	
Special provisions	

Sea transport

EmS	F-D, S-U
Special provisions	63 - 190 - 277 - 327 - 344 - 959
Limited quantities	1L
Contaminated packaging: Instructions	P207 - LP02
Contaminated packaging: Special provisions	PP87 - L2
IBC: Instructions	-
IBC: Provisions	-
Tank instructions IMO	-
Tank instructions UN	-
Tank instructions Special provisions	-
Stowage and segregation	SW1 - SW22 SG69
Properties and observations	
Remarks	
EQ	E0

Air transport

Hazard	-
Passenger	203 (75 kg)
Passenger LQ	Y203 (30 kg G)
Cargo	203 (150 kg)
ERG	10L

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

AEROSPRAY fixative for pastels / water-colours

Article No.		Issue date:	08.12.16
Version	4 (08.12.16)	Page	8 / 9

Remarks

EQ
Special Provisioning A145 - A167 - A802

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Europe

Contents of VOC [%]
Contents of VOC
[g/L]
Further regulations, limitations and legal requirements

Germany

Storage class
Water Hazard Class 1
WGK catalog number
Incident regulation
Information on working limitations
Further regulations, limitations and legal requirements

Denmark

Further regulations, limitations and legal requirements

Hungary

Further regulations, limitations and legal requirements

Great Britain

Further regulations, limitations and legal requirements

Switzerland

Contents of VOC [%]
ca. 97,4 %
Further regulations, limitations and legal requirements

USA

Further regulations, limitations and legal requirements
Federal Regulations
State Regulations

Japan

Further regulations, limitations and legal requirements

Canada

Further regulations, limitations and legal requirements

15.2 Chemical Safety Assessment

SECTION 16: Other information

Further information

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

AEROSPRAY fixative for pastels / water-colours

Article No.		Issue date:	08.12.16
Version	4 (08.12.16)	Page	9 / 9

Hazard statements (CLP)

- H220 Extremely flammable gas.
- H222 Extremely flammable aerosol.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H229 Pressurised container: May burst if heated.
- H280 Contains gas under pressure; may explode if heated.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.

Further information

This information is based on our current state of knowledge and describes the security standards applicable to our product for the purpose provided. The information provided here does not constitute a legally binding warranty of specific characteristics or of suitability for a specific application use of the product is thus to be adapted to the user's special conditions and checked by preliminary tests. We are thus unable to guarantee product characteristics or accept an liability for damage arising in connection with the use of our products.

Literature

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Reason of change

Additional information