



Safety Data Sheet

Copyright, 2014, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	27-7280-4	Version number:	4.00
Revision date:	26/11/2014	Supersedes date:	04/01/2013
Transportation version number:	1.00 (10/12/2010)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M Photomount (PL 9479)

Product Identification Numbers

YP-2080-6060-5 YP-2080-6063-9

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Adhesive aerosol.

1.3. Details of the supplier of the substance or mixture

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Aerosol, Category 1 - Aerosol 1; H222, H229
Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319
Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336
Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

Dangerous substances(67/548/EEC)/preparations(1999/45/EC) directive

Indication of danger

Extremely flammable; F+; R12

Irritant; Xi; R36

R66

R67

Dangerous for the environment; N; R51/53

For full text of R phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER!

Symbols:

GHS02 (Flame) |GHS07 (Exclamation mark) |GHS09 (Environment) |

Pictograms



Ingredient
Acetone

CAS Nbr
67-64-1

% by Wt
15 - 40

HAZARD STATEMENTS:

- H222 Extremely flammable aerosol.
- H319 Causes serious eye irritation.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H229 Pressurised container. may burst if heated.

- H411 Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

General:

- P102 Keep out of reach of children.
- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.

Prevention:

- P210A Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P273 Avoid release to the environment.

Response:

- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P332 + P313 If skin irritation occurs: Get medical advice/attention.

3M Photomount (PL 9479)

Storage:

P410 + P412

Protect from sunlight. Do not expose to temperatures exceeding 50C/122F.

Disposal:

P501

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

40% of the mixture consists of components of unknown acute oral toxicity.

Notes on labelling

H304 is not required on the label because the product is an aerosol.

Dangerous substances(67/548/EEC)/preparations(1999/45/EC) directive

Symbol(s)



Extremely
Flammable



Irritant



Dangerous
for the
environment

Contains:

No ingredients are assigned to the label.

Risk phrases

R12	Extremely flammable.
R36	Irritating to eyes.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.
R51/53	Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

Safety phrases

S16	Keep away from sources of ignition - No Smoking.
S23C	Do not breathe vapour or spray.
S51	Use only in well ventilated areas.
S29	Do not empty into drains.
S61	Avoid release to the environment. Refer to special instructions/safety data sheets.
S2	Keep out of the reach of children.

Special provisions concerning the labelling of certain substances

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.

Notes on labelling

R65 is not required on the label because the product is an aerosol.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

3M Photomount (PL 9479)

Ingredient	CAS Nbr	EU Inventory	% by Wt	Classification
Acetone	67-64-1	EINECS 200-662-2	15 - 40	F:R11; Xi:R36; R66; R67 (EU) Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336; EUH066 (CLP)
Propane	74-98-6	EINECS 200-827-9	25 - 35	F+:R12 (EU) Flam. Gas 1, H220; Liquified gas, H280 - Nota U (CLP)
Non-volatiles	Trade Secret		10 - 30	
Cyclohexane	110-82-7	EINECS 203-806-2	10 - 30	F:R11; Xn:R65; Xi:R38; N:R50/53; R67 - Nota 4 (EU) Flam. Liq. 2, H225; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336; Aquatic Acute 1, H400,M=1; Aquatic Chronic 1, H410,M=1 (CLP)
Non hazardous ingredients	Mixture		1 - 2	

Please see section 16 for the full text of any R phrases and H statements referred to in this section

Please refer to section 15 for the any applicable Notas that have been applied to the above components

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. Get medical attention.

Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

SECTION 5: Fire-fighting measures**5.1. Extinguishing media**

Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

3M Photomount (PL 9479)

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Hydrocarbons.	During combustion.
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.

5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Cover spill area with a fire-extinguishing foam. An appropriate aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Cyclohexane	110-82-7	UK HSC	TWA:350 mg/m ³ (100 ppm);STEL:1050 mg/m ³ (300 ppm)	
Acetone	67-64-1	UK HSC	TWA:1210 mg/m ³ (500 ppm);STEL:3620 mg/m ³ (1500 ppm)	
Propane	74-98-6	UK HSC	Limit value not established:	asphyxiant

UK HSC : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Aerosol
Appearance/Odour	Mild solvent odour; Clear mist
Odour threshold	<i>No data available.</i>
pH	<i>Not applicable.</i>
Boiling point/boiling range	<i>Not applicable.</i>
Melting point	<i>Not applicable.</i>
Flammability (solid, gas)	Not applicable.
Explosive properties	Not classified
Oxidising properties	Not classified
Flash point	-47 °C
Autoignition temperature	<i>No data available.</i>
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Relative density	0.70 [<i>Ref Std:WATER=1</i>]
Water solubility	Negligible
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Evaporation rate	<i>No data available.</i>
Vapour density	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity	<i>Not applicable.</i>
Density	0.7 kg/m ³

9.2. Other information

Volatile organic compounds (VOC)	590 g/l
Percent volatile	84.3 % weight [<i>Test Method:Estimated</i>]
VOC less H ₂ O & exempt solvents	<i>No data available.</i>

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Sparks and/or flames.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Intentional concentration and inhalation may be harmful or fatal. Simple asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause target organ effects after inhalation.

Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause target organ effects after ingestion.

Target Organ Effects:

Single exposure may cause:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Single exposure, above recommended guidelines, may cause:

Cardiac sensitisation: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Propane	Inhalation-Gas (4 hours)	Rat	LC50 > 200,000 ppm
Acetone	Dermal	Rabbit	LD50 > 15,688 mg/kg
Acetone	Inhalation-Vapor (4 hours)	Rat	LC50 76 mg/l
Acetone	Ingestion	Rat	LD50 5,800 mg/kg
Cyclohexane	Dermal	Rat	LD50 > 2,000 mg/kg

3M Photomount (PL 9479)

Cyclohexane	Inhalation-Vapor (4 hours)	Rat	LC50 > 32.9 mg/l
Cyclohexane	Ingestion	Rat	LD50 6,200 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Propane	Rabbit	Minimal irritation
Acetone	Mouse	Minimal irritation
Cyclohexane	Rabbit	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value
Propane	Rabbit	Mild irritant
Acetone	Rabbit	Severe irritant
Cyclohexane	Rabbit	Mild irritant

Skin Sensitisation

Name	Species	Value
------	---------	-------

Respiratory Sensitisation

Name	Species	Value
------	---------	-------

Germ Cell Mutagenicity

Name	Route	Value
Propane	In Vitro	Not mutagenic
Acetone	In vivo	Not mutagenic
Acetone	In Vitro	Some positive data exist, but the data are not sufficient for classification
Cyclohexane	In Vitro	Not mutagenic
Cyclohexane	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Acetone	Not specified.	Multiple animal species	Not carcinogenic

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Acetone	Ingestion	Not toxic to female reproduction	Mouse	NOAEL 11,298 mg/kg/day	13 weeks
Acetone	Ingestion	Some positive male reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,700 mg/kg/day	13 weeks
Acetone	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 5.2 mg/l	during organogenesis
Cyclohexane	Inhalation	Not toxic to female reproduction	Rat	NOAEL 24 mg/l	2 generation
Cyclohexane	Inhalation	Not toxic to male reproduction	Rat	NOAEL 24 mg/l	2 generation
Cyclohexane	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 6.9 mg/l	2 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Propane	Inhalation	cardiac sensitization	Causes damage to organs	Human	NOAEL Not available	
Propane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Propane	Inhalation	respiratory irritation	All data are negative	Human	NOAEL Not available	
Acetone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Acetone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Acetone	Inhalation	immune system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL 1.19 mg/l	6 hours
Acetone	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Guinea pig	NOAEL Not available	
Acetone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Cyclohexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Cyclohexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Acetone	Dermal	eyes	Some positive data exist, but the data are not sufficient for classification	Guinea pig	NOAEL Not available	3 weeks
Acetone	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL 3 mg/l	6 weeks
Acetone	Inhalation	immune system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL 1.19 mg/l	6 days
Acetone	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Guinea pig	NOAEL 119 mg/l	not available
Acetone	Inhalation	heart liver	All data are negative	Rat	NOAEL 45 mg/l	8 weeks
Acetone	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 900 mg/kg/day	13 weeks
Acetone	Ingestion	heart	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Acetone	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 200 mg/kg/day	13 weeks
Acetone	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 3,896 mg/kg/day	14 days
Acetone	Ingestion	eyes	All data are negative	Rat	NOAEL 3,400 mg/kg/day	13 weeks
Acetone	Ingestion	respiratory system	All data are negative	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Acetone	Ingestion	muscles	All data are negative	Rat	NOAEL 2,500 mg/kg	13 weeks

3M Photomount (PL 9479)

Acetone	Ingestion	skin bone, teeth, nails, and/or hair	All data are negative	Mouse	NOAEL 11,298 mg/kg/day	13 weeks
Cyclohexane	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 24 mg/l	90 days
Cyclohexane	Inhalation	auditory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.7 mg/l	90 days
Cyclohexane	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rabbit	NOAEL 2.7 mg/l	10 weeks
Cyclohexane	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 24 mg/l	14 weeks
Cyclohexane	Inhalation	peripheral nervous system	All data are negative	Rat	NOAEL 8.6 mg/l	30 weeks

Aspiration Hazard

Name	Value
Cyclohexane	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Non-volatiles	Trade Secret		Data not available or insufficient for classification			
Propane	74-98-6		Data not available or insufficient for classification			
Cyclohexane	110-82-7	Green algae	Experimental	72 hours	EC50	3.4 mg/l
Cyclohexane	110-82-7	Water flea	Experimental	48 hours	EC50	0.9 mg/l
Cyclohexane	110-82-7	Fathead minnow	Experimental	96 hours	LC50	4.53 mg/l
Acetone	67-64-1	Water flea	Experimental	48 hours	EC50	13,500 mg/l
Acetone	67-64-1	Rainbow trout	Experimental	96 hours	LC50	5,540 mg/l
Acetone	67-64-1	Green Algae	Experimental	96 hours	EC50	2,574 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Non-volatiles	Trade Secret	Data not available or	N/A	N/A	N/A	N/A

3M Photomount (PL 9479)

		insufficient for classification				
Propane	74-98-6	Experimental Photolysis		Photolytic half-life (in air)	27.5 days (t 1/2)	Other methods
Cyclohexane	110-82-7	Experimental Photolysis		Photolytic half-life (in air)	4.14 days (t 1/2)	Other methods
Cyclohexane	110-82-7	Experimental Biodegradation	28 days	BOD	77 % weight	OECD 301F - Manometric respirometry
Acetone	67-64-1	Estimated Photolysis		Photolytic half-life (in air)	80 days (t 1/2)	Other methods
Acetone	67-64-1	Experimental Photolysis		Photolytic half-life (in air)	146.5 days (t 1/2)	Other methods
Acetone	67-64-1	Experimental Biodegradation	28 days	BOD	96 % weight	OECD 301C - MITI test (I)

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Non-volatiles	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Propane	74-98-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Cyclohexane	110-82-7	Experimental BCF - Other	56 days	Bioaccumulation factor	<129	Other methods
Acetone	67-64-1	Experimental BCF - Other		Bioaccumulation factor	0.65	Other methods
Acetone	67-64-1	Experimental Bioconcentration		Log Kow	-0.24	Other methods

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

No information available at this time, contact manufacturer for more details

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

See Section 11.1 Information on toxicological effects

Dispose of waste product in a permitted industrial waste facility. Facility must be capable of handling aerosol cans. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the

3M Photomount (PL 9479)

available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

- 08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances
- 16 05 04* Gases in pressure containers (including halons) containing dangerous substances
- 20 01 27* Paint, inks, adhesives and resins containing dangerous substances

EU waste code (product container after use)

- 15 01 04 Metallic packaging

SECTION 14: Transportation information

YP-2080-6060-5, YP-2080-6063-9

ADR/RID: UN1950, AEROSOLS, LIMITED QUANTITY, 2.1, (E), ADR Classification Code: 5F.

IMDG-CODE: UN1950, AEROSOLS, 2.1, IMDG-Code segregation code: NONE, LIMITED QUANTITY, EMS: FD,SU.

ICAO/IATA: UN1950, AEROSOLS, FLAMMABLE, 2.1.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information.

15.2. Chemical Safety Assessment

Not applicable

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container. may burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

List of relevant R-phrases

R11	Highly flammable.
-----	-------------------

R12	Extremely flammable.
R36	Irritating to eyes.
R38	Irritating to skin.
R50/53	Very toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.
R51/53	Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.
R65	Harmful: May cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

Revision information:

Revision Changes:

Section 1: Product identification numbers heading information was modified.
Section 16: List of relevant R phrase information information was modified.
Section 12: Component ecotoxicity information information was modified.
Section 12: Persistence and Degradability information information was modified.
Section 12: Biocumulative potential information information was modified.
Copyright information was modified.
Section 8: Occupational exposure limit table information was modified.
OEL Reg Agency Desc information was modified.
Telephone header information was modified.
Company Telephone information was modified.
Section 11: Aspiration Hazard Table information was modified.
Section 11: Acute Toxicity table information was modified.
Section 11: Carcinogenicity Table information was modified.
Section 11: Serious Eye Damage/Irritation Table information was modified.
Section 11: Germ Cell Mutagenicity Table information was modified.
Section 11: Reproductive Toxicity Table information was modified.
Section 11: Skin Corrosion/Irritation Table information was modified.
Section 11: Target Organs - Repeated Table information was modified.
Section 11: Target Organs - Single Table information was modified.
Section 11: Health Effects - Inhalation information information was modified.
Section 6: Accidental release clean-up information information was modified.
Section 7: Precautions safe handling information information was modified.
Section 8: Appropriate Engineering controls information information was modified.
Section 8: Personal Protection - Eye information information was modified.
Section 8: Personal Protection - Skin/hand information information was modified.
Section 13: 13.1. Waste disposal note information was modified.
Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.
Label: Signal Word - Header information was added.
Label: Signal Word information was added.
Label: CLP Classification - Header information was added.
Label: CLP Classification information was added.
Label: CLP Classification information was added.
Label: CLP Classification - Header information was added.
Label: CLP Percent Unknown information was added.
Label: CLP Environmental Hazard Statements information was added.
Label: Graphic information was added.
Label: Graphic information was added.
Label: Symbol information was added.
Label: Symbol information was added.
Label: CLP Precautionary - Disposal information was added.
Label: CLP Precautionary - Disposal - Header information was added.
Label: CLP Precautionary - General information was added.
Label: CLP Precautionary - General - Header information was added.
Label: CLP Precautionary - Prevention information was added.

Label: CLP Precautionary - Prevention - Header information was added.
Label: CLP Precautionary - Response information was added.
Label: CLP Precautionary - Response - Header information was added.
Label: CLP Precautionary - Storage information was added.
Label: CLP Precautionary - Storage - Header information was added.
Label: Precautionary Statement - Header information was added.
CLP: Ingredient table information was added.
Section 2: Notes on labelling heading information was added.
Section 8: Occupational exposure limit table information was added.
CLP Remark(phrase) information was added.
Section 2: 2.2 & 2.3. CLP REGULATION heading information was added.
Section 8: Personal Protection - Respiratory Information information was added.
Label: CLP Ingredients table Ingredient heading information was added.
Label: CLP Ingredients table CAS No heading information was added.
Label: CLP Ingredients table Percent by Wt heading information was added.
Section 9: Odour Threshold information was added.
Section 9: Solubility (non-water) information was added.
Section 09: Decomposition Temperature information was added.
Section 11: Single exposure may cause: heading information was added.
Section 11: Single exposure may cause standard phrases information was added.
Section 2: H phrase reference information was added.
Section 10: Hazardous decomposition products during combustion text information was added.
Section 11: Disclosed components not in tables text information was added.
Section 12: Classification Warning information was added.
Section 11: Classification disclaimer information was added.
Section 8: 8.1.1 Biological limit values table heading information was added.
Section 8: BLV information was added.
Section 8: glove data - Material heading information was added.
Section 8: glove data - Thickness heading information was added.
Section 8: glove data - Breakthrough Time heading information was added.
Section 8: glove data value information was added.
Section 8: Skin protection - recommended gloves information information was deleted.
Section 8: Eye/face protection text information was deleted.
Section 8: Respiratory protection - recommended respirators information was deleted.
Section 12: Acute aquatic hazard information information was deleted.
Section 12: Chronic aquatic hazard heading information was deleted.
Section 12: Acute aquatic hazard heading information was deleted.
Section 12: Chronic aquatic hazard information information was deleted.
Section 8: mg/m³ key information was deleted.
Section 8: ppm key information was deleted.
Section 11: Classification disclaimer information was deleted.
Section 11: Skin Sensitization Table information was deleted.
Section 11: Respiratory Sensitization Table information was deleted.
Section 11: Health Effects - Other information information was deleted.
Section 12: Classification Warning information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M United Kingdom MSDSs are available at www.3M.com/uk