Safety data sheet in accordance with regulation	(EC) No 1907/2006
---	-------------------

Trade name: Marabu do it Satin Matt 073, 150 ml

ate revised: (

Substance number: 21070006073

Version: 4 / GB Replaces Version: 3 / GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Marabu do it Satin Matt 073, 150 ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/preparation

- Colour spray
- Identified Uses

Consumer uses: Private households (= general public = consumers) Coatings and paints, thinners, paint removers

1.3. Details of the supplier of the safety data sheet

Address

PC9a

Marabu GmbH & Co. k	G
Asperger Strasse 4	
71732 Tamm	
Germany	
Telephone no.	+49-7141/691-0
Fax no.	+49-7141/691-147
Information provided	Department product safety
by / telephone	
E-mail address of	PRSI@marabu.de
person responsible	
for this SDS	

1.4. Emergency telephone number

(+49) (0)621-60-43333

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture


Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)

H222
H229
H319
H336

2.2. Label elements

Labelling according to regulation (EC) No 1272/2008



Safety data sheet in	n accordance with re	egulation (EC)	NO 1907			
Trade name: Marab	u do it Satin Matt 073	3 150 ml				
made name. marab		Version:	4 / GB			Date revised: 09.07.2
Substance number:	21070006073	Replaces	s Version	n: 3/GB		Print date: 13.0
H229	Pressuris	sed container: N	/lay burst	if heated		
H319		serious eye irrita				
H336	May cau	se drowsiness o	or dizzine	ess.		
Precautional	ry statements					
P101	If medica	al advice is need	ded, have	e product o	container o	r label at hand.
P102	Keep out	t of reach of chil	dren.			
P210	sources.	No smoking.		•		nes and other ignition
P211		pray on an oper			nition source	е.
P251		ierce or burn, ev				
P264.1		nds thoroughly				
P271		outdoors or in a				ion/fooo protoction
P280 P305+P351						ion/face protection. inutes. Remove contact
F 300+F 30		present and ea				
P405	Store loc		isy io uo.		, mong.	
P410+P412			o not exp	ose to ten	nperatures	exceeding 50 °C/122°F.
P501.9		of contents/con				oncood
Hazardous d	omponent(s) to b					lo. 1272/2008)
contains	• • • •		-	-	. ,	1-methylethyl acetate
	•		SI,IT Duty	1 0001010,2		r meanyleanyl doctate
	al information					
		1		1.1.1.1.1.1.1.1.1		
EUH066 Further supp	Repeate clemental informa	d exposure may tion	/ cause s	kin dryne:	ss or cracki	ng.
Further supp Without add 2.3. Other haza No special	blemental informa equate ventilation, ex rds hazards have to be n	tion plosive atmospl nentioned.	here/gas	mix may l	be created.	ng.
Further supp Without add 2.3. Other hazan No special SECTION 3: C	blemental informa equate ventilation, ex rds hazards have to be n	tion plosive atmospl nentioned.	here/gas	mix may l	be created.	ng.
Further supp Without add 2.3. Other hazar No special SECTION 3: C 3.2. Mixtures	olemental informa equate ventilation, ex rds hazards have to be n omposition/in	tion plosive atmospl nentioned.	here/gas	mix may l	be created.	ng.
Further supp Without add 2.3. Other hazar No special SECTION 3: C 3.2. Mixtures Chemical ch	olemental informate equate ventilation, ex rds hazards have to be m omposition/in aracterization	tion plosive atmospl nentioned.	here/gas	mix may l	be created.	ng.
Further supp Without add 2.3. Other hazar No special SECTION 3: C 3.2. Mixtures Chemical ch	olemental informa equate ventilation, ex rds hazards have to be n omposition/in	tion plosive atmospl nentioned.	here/gas	mix may l	be created.	ng.
Further supp Without add 2.3. Other hazar No special SECTION 3: C 3.2. Mixtures Chemical ch	olemental informate equate ventilation, ex rds hazards have to be m omposition/in aracterization sed colour spray	tion plosive atmospl nentioned.	here/gas	mix may l	be created.	ng.
Further supp Without add 2.3. Other hazar No special SECTION 3: C 3.2. Mixtures Chemical ch Solvent bas Hazardous in	blemental informate equate ventilation, ex rds hazards have to be m omposition/in aracterization sed colour spray ngredients	tion plosive atmospl nentioned.	here/gas	mix may l	be created.	ng.
Further supp Without add 2.3. Other hazar No special SECTION 3: C 3.2. Mixtures Chemical ch Solvent bas	blemental informate equate ventilation, ex rds hazards have to be m omposition/in aracterization sed colour spray ngredients	tion plosive atmospl nentioned. formation	here/gas	mix may l	be created.	ng.
Further supp Without add 2.3. Other hazar No special SECTION 3: C 3.2. Mixtures Chemical ch Solvent bas Hazardous in Ethyl acetate	olemental informate equate ventilation, ex rds hazards have to be m omposition/in aracterization sed colour spray ngredients a 141-78-6	tion plosive atmospl nentioned. formation	here/gas	mix may l	be created.	ng.
Further supp Without add 2.3. Other hazar No special SECTION 3: C 3.2. Mixtures Chemical ch Solvent bas Hazardous in Ethyl acetate CAS No.	blemental informate equate ventilation, ex rds hazards have to be m omposition/in aracterization sed colour spray ngredients a 141-78-6 205-500	tion plosive atmospl nentioned. formation	here/gas	mix may l	be created.	ng.
Further supp Without add 2.3. Other hazar No special SECTION 3: C 3.2. Mixtures Chemical ch Solvent bas Hazardous in Ethyl acetate CAS No. EINECS no	blemental informate equate ventilation, ex rds hazards have to be m omposition/in aracterization sed colour spray ngredients 141-78-6 205-500- n no. 01-2119	tion plosive atmospl nentioned. formation	here/gas	mix may l	be created.	ng.
Further supp Without add 2.3. Other hazar No special SECTION 3: C 3.2. Mixtures Chemical ch Solvent bas Hazardous in Ethyl acetate CAS No. EINECS no Registratior Concentrati	blemental informate equate ventilation, ex rds hazards have to be m omposition/in aracterization sed colour spray ngredients a 141-78-6 b 205-500- n no. 01-2119- ion >=	tion plosive atmospl nentioned. formation formation 4 475103-46 10	nere/gas <u>on ing</u>	mix may l	be created. D ts ***	ng.
Further supp Without add 2.3. Other hazar No special SECTION 3: C 3.2. Mixtures Chemical ch Solvent bas Hazardous in Ethyl acetate CAS No. EINECS no Registratior Concentrati	blemental informate equate ventilation, ex rds hazards have to be m omposition/in aracterization sed colour spray ngredients a 141-78-6 b. 205-500- b no. 01-2119- ion >= on (Regulation (EC) N	tion plosive atmospl nentioned. formation formation 4 475103-46 10 No. 1272/2008)	on ing	mix may l	be created. D ts ***	ng.
Further supp Without add 2.3. Other hazar No special SECTION 3: C 3.2. Mixtures Chemical ch Solvent bas Hazardous in Ethyl acetate CAS No. EINECS no Registratior Concentrati	blemental informate equate ventilation, ex rds hazards have to be m omposition/in aracterization sed colour spray ngredients a 141-78-6 b. 205-500- bn no. 01-21194 ion >= on (Regulation (EC) N Flam. Lic	tion plosive atmospl nentioned. formation formation 4 475103-46 10 No. 1272/2008) J. 2	on ing < H225	mix may l	be created. D ts ***	ng.
Further supp Without add 2.3. Other hazar No special SECTION 3: C 3.2. Mixtures Chemical ch Solvent bas Hazardous in Ethyl acetate CAS No. EINECS no Registratior Concentrati	blemental informate equate ventilation, ex rds hazards have to be m omposition/in aracterization sed colour spray ngredients a 141-78-6 b. 205-500- b no. 01-2119- ion >= on (Regulation (EC) N	tion plosive atmospl mentioned. formation formation formation 10 4 475103-46 10 No. 1272/2008) 1. 2 2	on ing	mix may l	be created. D ts ***	ng.
Further supp Without add 2.3. Other hazar No special SECTION 3: C 3.2. Mixtures Chemical ch Solvent bas Hazardous in Ethyl acetate CAS No. EINECS no Registratior Concentrati	blemental informate equate ventilation, ex rds hazards have to be m omposition/in aracterization sed colour spray ngredients a 141-78-6 b 205-500- n no. 01-21194 ion >= on (Regulation (EC) N Flam. Lic Eye Irrit.	tion plosive atmospl mentioned. formation formation formation 10 4 475103-46 10 No. 1272/2008) 1. 2 2	on ing < H225 H319	mix may l	be created. D ts ***	ng.
Further supp Without add 2.3. Other hazar No special SECTION 3: C 3.2. Mixtures Chemical ch Solvent bas Hazardous if Ethyl acetate CAS No. EINECS no Registration Concentrati	blemental informate equate ventilation, ex rds hazards have to be m omposition/in aracterization sed colour spray ngredients a 141-78-6 b 205-500- n no. 01-21194 ion >= on (Regulation (EC) N Flam. Lic Eye Irrit.	tion plosive atmospl mentioned. formation formation formation 10 4 475103-46 10 No. 1272/2008) 1. 2 2	on ing < H225 H319	mix may l	be created. D ts ***	ng.
Further supp Without add 2.3. Other hazar No special SECTION 3: C 3.2. Mixtures Chemical ch Solvent bas Hazardous in Ethyl acetate CAS No. EINECS no Registratior Concentrati	blemental informate equate ventilation, ex rds hazards have to be m omposition/in aracterization sed colour spray ngredients a 141-78-6 b 205-500- n no. 01-21194 ion >= on (Regulation (EC) N Flam. Lic Eye Irrit.	tion plosive atmospl mentioned. formation formation formation 10 4 475103-46 10 No. 1272/2008) 1. 2 2	on ing < H225 H319	mix may l	be created. D ts ***	ng.
Further supp Without add 2.3. Other hazar No special SECTION 3: C 3.2. Mixtures Chemical ch Solvent bas Hazardous in Ethyl acetate CAS No. EINECS no Registration Concentrati	blemental informate equate ventilation, ex rds hazards have to be m omposition/in aracterization sed colour spray ngredients an 141-78-6 b. 205-500- n no. 01-2119- ion >= on (Regulation (EC) N Flam. Lic Eye Irrit. STOT SE	tion plosive atmospl mentioned. formation formation 4475103-46 10 No. 1272/2008) 1. 2 2 3	on ing < H225 H319	mix may l	be created. D ts ***	ng.
Further supp Without add 2.3. Other hazar No special SECTION 3: C 3.2. Mixtures Chemical ch Solvent bas Hazardous in Ethyl acetate CAS No. EINECS no Registration Concentrati Classification Concentrati	olemental informate equate ventilation, ex rds hazards have to be m omposition/in aracterization sed colour spray ngredients ano. 01-21194 ion con (Regulation (EC) N Flam. Lic Eye Irrit. STOT SE 67-63-0 200-661-	tion plosive atmospl mentioned. formation formation 4475103-46 10 No. 1272/2008) 1. 2 2 3	on ing < H225 H319	mix may l	be created. D ts ***	ng.
Further supp Without add 2.3. Other hazar No special SECTION 3: C 3.2. Mixtures Chemical ch Solvent bas Hazardous in Ethyl acetate CAS No. EINECS no Registration Concentrati Classification Propan-2-ol CAS No. EINECS no EINECS no	olemental informate equate ventilation, ex rds hazards have to be m omposition/in earacterization sed colour spray ngredients earacterization sed colour spray ngredients earacterization sed colour spray ngredients earacterization on no. 01-21194 ion >= on (Regulation (EC) N Flam. Lic Eye Irrit. STOT SE 67-63-0 0. 200-661- no. 01-21194	tion plosive atmosple mentioned. formation for	on ing < H225 H319	mix may l	be created. D ts ***	ng.
Further supp Without add 2.3. Other hazar No special SECTION 3: C 3.2. Mixtures Chemical ch Solvent bas Hazardous in Ethyl acetate CAS No. EINECS no Registration Concentration Classification CAS No. EINECS no Registration Concentration	olemental informate equate ventilation, ex rds hazards have to be m omposition/in aracterization sed colour spray ngredients ano. 01-21194 ion on (Regulation (EC) N Flam. Lic Eye Irrit. STOT SE 67-63-0 on 01-21194 ion >= 67-63-0 o. 200-661- on 01-21194 ion >=	tion plosive atmosple mentioned. formation formatio formation formation formation formation formation form	on ing < H225 H319 H336	mix may l gredien	be created. hts *** %	ng.
Further supp Without add 2.3. Other hazar No special SECTION 3: C 3.2. Mixtures Chemical ch Solvent bas Hazardous in Ethyl acetate CAS No. EINECS no Registration Concentration Classification CAS No. EINECS no Registration Concentration	olemental informate equate ventilation, ex rds hazards have to be m omposition/in earacterization sed colour spray ngredients ano. 01-21194 ion pon (Regulation (EC) N Flam. Lic Eye Irrit. STOT SE on 01-21194 ion pon (Regulation (EC) N Flam. Lic Eye Irrit. STOT SE on no. 01-21194 ion pon (Regulation (EC) N for no. 01-21194 ion >= on (Regulation (EC) N	tion plosive atmospl mentioned. formation form	on ing < H225 H319 H336 <	mix may l gredien	be created. hts *** %	ng.
Further supp Without add 2.3. Other hazar No special SECTION 3: C 3.2. Mixtures Chemical ch Solvent bas Hazardous in Ethyl acetate CAS No. EINECS no Registration Concentration Classification CAS No. EINECS no Registration Concentration	olemental informate equate ventilation, ex rds hazards have to be m omposition/in aracterization sed colour spray ngredients ano. 01-21194 ion on (Regulation (EC) N Flam. Lic Eye Irrit. STOT SE 67-63-0 on 01-21194 ion >= 67-63-0 o. 200-661- on 01-21194 ion >=	tion plosive atmosple mentioned. formation formatio formation formation formation formation formation form	on ing < H225 H319 H336	mix may l gredien	be created. hts *** %	ng.

ade name: Marabu do it Sati		ion: 4/GB			Date revised	Maral 1: 09.07.201
ubstance number: 21070006	6073 Repl	aces Versior	n: 3/GE	3		date: 13.07.1
	STOT SE 3	H336				
n-Butyl acetate CAS No. EINECS no. Registration no. Concentration	123-86-4 204-658-1 01-2119485493-29 >= 1	<	10	%		
Classification (Regula	tion (EC) No. 1272/20 Flam. Liq. 3 STOT SE 3	08) H226 H336				
2-Butoxyethanol CAS No. EINECS no. Registration no. Concentration	111-76-2 203-905-0 01-2119475108-36 >= 1	<	10	%		
Classification (Regula	tion (EC) No. 1272/20 Skin Irrit. 2 Acute Tox. 4 Acute Tox. 4 Acute Tox. 4 Eye Irrit. 2	08) H315 H332 H312 H302 H319				
2-Methoxy-1-methyletl CAS No. EINECS no. Registration no. Concentration	nyl acetate 108-65-6 203-603-9 01-2119475791-29 >= 1	<	10	%		
Classification (Regula	tion (EC) No. 1272/20 Flam. Liq. 3 STOT SE 3	08) H226 H336				
Further ingredients **	**					
Hydrocarbons, C3-4; F CAS No. EINECS no. Registration no. Concentration	68476-40-4 270-681-9	<	50	%	[3]	
Classification (Regula	tion (EC) No. 1272/20 Flam. Gas 1 Press. Gas	08) H220 H280				
[3] Substance with oc	cupational exposure lir	mits				

Trade name: Marabu do it Satin Matt 073, 150 ml

Version: 4 / GB

Substance number: 21070006073

Replaces Version: 3 / GB

General information

In all cases of doubt, or when symptoms persist, seek medical attention. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Summon a doctor immediately.

After skin contact

After contact with skin, wash immediately with plenty of water. Don't use solvents.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

Summon a doctor immediately. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed Until now no symptoms known so far.

4.3. Indication of any immediate medical attention and special treatment needed

Hints for the physician / treatment

Treat symptomatically

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Recommended: alcohol resistant foam, CO2, powders, water spray/mist, Not be used for safety reasons: water jet

5.2. Special hazards arising from the substance or mixture

In the event of fire the following can be released: Carbon monoxide (CO); Carbon dioxide (CO2); dense black smoke

5.3. Advice for firefighters

Special protective equipment for fire-fighting

In case of combustion use a suitable breathing apparatus.

Other information

Cool endangered containers with water spray jet. Collect contaminated fire-fighting water separately, must not be discharged into the drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away sources of ignition. Ensure adequate ventilation. Do not breathe gas/fumes/vapour/spray. Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4. Reference to other sections

Trade name: Marabu do it Satin Matt 073, 150 ml

Version: 4 / GB

Substance number: 21070006073

Replaces Version: 3 / GB

Refer to protective measures listed in Sections 7 and 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Provide good ventilation of working area (local exhaust ventilation if necessary). Handle and open container with care. Isolate from sources of heat, sparks and open flame. Avoid skin and eye contact. Smoking, eating and drinking shall be prohibited in application area. Comply with the health and safety at work laws.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge.

Classification of fires / temperature class / Ignition group / Dust explosion class

C (Flammable gases)

Classification of fires Temperature class

7.2. Conditions for safe storage, including any incompatibilities

T2

Requirements for storage rooms and vessels

Store in accordance with national regulation

Further information on storage conditions

Keep away from sources of ignition. Keep container in a cool, well-ventilated place. Observe label precautions.

7.3. Specific end use(s)

Colour spray

SECTION 8: Exposure controls/personal protection ***

8.1. Control parameters

Exposure limit values ***

Ethyl acetate				
List	EH40			
Туре	WEL			
Value			200	ppm(V)
Short term exposure limit			400	ppm(V)
Status: 2011				
2-Methoxy-1-methylethyl acetat	e			
List	EH40			
Туре	WEL			
Value	274	mg/m³	50	ppm(V)
Short term exposure limit	548	mg/m³	100	ppm(V)
Skin resorption / sensibilisation:	Sk; Stat	us: 2011		
Propan-2-ol				
List	EH40			
Туре	WEL			
Value	999	mg/m³	400	ppm(V)
Short term exposure limit	1250	mg/m³	500	ppm(V)
Status: 2011				
2-Butoxyethanol				
List	EH40			
Туре	WEL			
Value			25	ppm(V)

Substance number: 21070006073 Short term exposure limit Skin resorption / sensibilisation n-Butyl acetate List Type Value Short term exposure limit Status: 2011 Derived No/Minimal Effect Le Hydrocarbons, C3-4; Petroleum Type of value Reference group Duration of exposure Route of exposure Mode of action Concentration Type of value Reference group Duration of exposure	Rep : Sk; Sta EH40 WEL 724 966 vels (DNE n gas Derived N Worker Long terr inhalative Systemic	rsion: 4 / GB blaces Version: tus: 2011 mg/m ³ mg/m ³ EL/DMEL) ***	3 / GB 50 150 200		d: 09.07.2019 date: 13.07.19
Short term exposure limit Skin resorption / sensibilisation n-Butyl acetate List Type Value Short term exposure limit Status: 2011 Derived No/Minimal Effect Le Hydrocarbons, C3-4; Petroleum Type of value Reference group Duration of exposure Route of exposure Mode of action Concentration Type of value Reference group	: Sk; Sta EH40 WEL 724 966 vels (DNE n gas Derived I Worker Long terr inhalative Systemic	tus: 2011 mg/m³ mg/m³ EL/DMEL) ***	50 150	ppm(V) ppm(V)	date: 13.07.1§
Skin resorption / sensibilisation n-Butyl acetate List Type Value Short term exposure limit Status: 2011 Derived No/Minimal Effect Le Hydrocarbons, C3-4; Petroleum Type of value Reference group Duration of exposure Route of exposure Mode of action Concentration Type of value Reference group	EH40 WEL 724 966 vels (DNE n gas Derived I Worker Long terr inhalative Systemic	mg/m³ mg/m³ EL/DMEL) ***	150	ppm(V)	
n-Butyl acetate List Type Value Short term exposure limit Status: 2011 Derived No/Minimal Effect Le Hydrocarbons, C3-4; Petroleum Type of value Reference group Duration of exposure Route of exposure Mode of action Concentration Type of value Reference group	EH40 WEL 724 966 vels (DNE n gas Derived I Worker Long terr inhalative Systemic	mg/m³ mg/m³ EL/DMEL) ***			
List Type Value Short term exposure limit Status: 2011 Derived No/Minimal Effect Le Hydrocarbons, C3-4; Petroleum Type of value Reference group Duration of exposure Route of exposure Mode of action Concentration Type of value Reference group	WEL 724 966 vels (DNE n gas Derived I Worker Long terr inhalative Systemic	mg/m ³ E L/DMEL) ***			
List Type Value Short term exposure limit Status: 2011 Derived No/Minimal Effect Le Hydrocarbons, C3-4; Petroleum Type of value Reference group Duration of exposure Route of exposure Mode of action Concentration Type of value Reference group	WEL 724 966 vels (DNE n gas Derived I Worker Long terr inhalative Systemic	mg/m ³ E L/DMEL) ***			
Value Short term exposure limit Status: 2011 Derived No/Minimal Effect Le Hydrocarbons, C3-4; Petroleum Type of value Reference group Duration of exposure Route of exposure Mode of action Concentration Type of value Reference group	724 966 vels (DNE n gas Derived I Worker Long terr inhalative Systemic	mg/m ³ E L/DMEL) ***			
Short term exposure limit Status: 2011 Derived No/Minimal Effect Le Hydrocarbons, C3-4; Petroleum Type of value Reference group Duration of exposure Route of exposure Mode of action Concentration Type of value Reference group	966 vels (DNE n gas Derived I Worker Long terr inhalative Systemic	mg/m ³ E L/DMEL) ***			
Status: 2011 Derived No/Minimal Effect Le Hydrocarbons, C3-4; Petroleum Type of value Reference group Duration of exposure Route of exposure Mode of action Concentration Type of value Reference group	vels (DNE n gas Derived I Worker Long terr inhalative Systemic	EL/DMEL) ***	200	ppm(V)	
Hydrocarbons, C3-4; Petroleum Type of value Reference group Duration of exposure Route of exposure Mode of action Concentration Type of value Reference group	n gas Derived I Worker Long terr inhalative Systemic				
Type of value Reference group Duration of exposure Route of exposure Mode of action Concentration Type of value Reference group	Derived I Worker Long terr inhalative Systemic	Minimal Effect Le			
Reference group Duration of exposure Route of exposure Mode of action Concentration Type of value Reference group	Worker Long terr inhalative Systemic	Vinimal Effect Le			
Duration of exposure Route of exposure Mode of action Concentration Type of value Reference group	Long terr inhalative Systemic		evel (DMEL)		
Route of exposure Mode of action Concentration Type of value Reference group	inhalative Systemic				
Mode of action Concentration Type of value Reference group	Systemic				
Concentration Type of value Reference group	•				
Type of value Reference group	2				
Reference group	2	2,21		mg/m³	
Reference group	Derived I	No Effect Level (DNEL)		
	Worker		/		
	Long terr	n			
Route of exposure	dermal				
Mode of action	Systemic	effects			
Concentration		3,4		mg/kg/d	
Type of value	Derived I	Minimal Effect Le	evel (DMEL)		
Reference group	Consume		· · · ·		
Duration of exposure	Long terr	n			
Route of exposure	inhalative	;			
Mode of action	Systemic	effects			
Concentration	C	,066		mg/m³	
Ethyl acetate					
Type of value	Derived I	No Effect Level (DNEL)		
Reference group	Worker	,	,		
Duration of exposure	Acute				
Route of exposure	inhalative	;			
Concentration	1	468		mg/m³	
Type of value	Derived 1	No Effect Level (DNEL)		
Reference group	Worker		· · · = - - /		
Duration of exposure	Acute				
Route of exposure	inhalative	9			
Mode of action	Local effe				
Concentration		468		g/m³	
Type of value	Derived M	No Effect Level (
Reference group	Worker				
Route of exposure	dermal				
Mode of action	Chronic e	effects			
Concentration		3		mg/kg	
Type of value	Derived M	No Effect Level (
Reference group	Worker				
Route of exposure	inhalative	2			
Mode of action					
Concentration	Chronic e	ottects			

Trade name: Marabu do it Satin Matt 073, 150 ml Version: 4/GB Date revised: 09.07.2019 Substance number: 21070006073 Replaces Version: 3 / GB Type of value Derived No Effect Level (DNEL) Reference group Worker Route of exposure inhalative Mode of action Chronic effects Concentration 734 mg/m³ Type of value Derived No Effect Level (DNEL) Reference group Consumer Route of exposure inhalative Mode of action Acute effects Concentration 734 mg/m³

Print date: 13.07.19

Safety data sheet in accordance with regulation (EC) No 1907/2006

		5
Type of value Reference group Route of exposure Mode of action Concentration	Derived No Effect Level (DNEL) Consumer inhalative Local effects 734	mg/m³
Type of value Reference group Route of exposure Mode of action Concentration	Derived No Effect Level (DNEL) Consumer dermal Chronic effects 37	mg/kg
Type of value Reference group Route of exposure Mode of action Concentration	Derived No Effect Level (DNEL) Consumer inhalative Chronic effects 367	mg/m³
Type of value Reference group Route of exposure Mode of action Concentration	Derived No Effect Level (DNEL) Consumer oral Chronic effects 4,5	mg/m³
Type of value Reference group Route of exposure Mode of action Concentration	Derived No Effect Level (DNEL) Consumer inhalative Local effects 367	mg/m³
2-Methoxy-1-methylethyl ac Type of value Reference group Duration of exposure Route of exposure Mode of action Concentration	etate Derived No Effect Level (DNEL) Worker Long term dermal Systemic effects 796	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	

Type of value Reference group Worker Duration of exposure Long term Route of exposure inhalative Mode of action Systemic effects Concentration 275

mg/m³

rade name: Marabu do it Satin Matt (ΔV	
	Version: 4/GB	Marabu Date revised: 09.07.2019
Substance number: 21070006073	Replaces Version: 3 / GB	Print date: 13.07.19
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	320	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	m a / m 3
Concentration	33	mg/m³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	33	mg/m³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	36	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Lifetime	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	550	mg/m³
Propan-2-ol		
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	500	mg/m³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	888	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	

Safety data sheet in accordance with regulation (EC) No 1907/2006			
Trade name: Marabu do it Satin Matt (Marabu	
	Version: 4 / GB	Date revised: 09.07.2019	
Substance number: 21070006073	Replaces Version: 3 / GB	Print date: 13.07.19	
	Derived No Effect Level (DNEL)		
Type of value Reference group	Derived No Effect Level (DNEL) General Population		
Duration of exposure	Long term		
Route of exposure	dermal		
Mode of action	Systemic effects		
Concentration	319	mg/kg/d	
Type of value	Derived No Effect Level (DNEL)		
Reference group	General Population		
Duration of exposure	Long term		
Route of exposure	oral		
Mode of action	Systemic effects	malkald	
Concentration	26	mg/kg/d	
2-Butoxyethanol			
Type of value	Derived No Effect Level (DNEL)		
Reference group	Worker		
Duration of exposure	Acute		
Route of exposure Mode of action	dermal Svotomia offecto		
Concentration	Systemic effects 89	mg/kg	
Concentration	09	ilig/kg	
Type of value	Derived No Effect Level (DNEL)		
Reference group	Worker		
Duration of exposure	Short term		
Route of exposure	inhalative		
Mode of action Concentration	Systemic effects 1091	mg/m³	
Type of value	Derived No Effect Level (DNEL)		
Reference group	General Population		
Duration of exposure	Short term		
Route of exposure	inhalative		
Mode of action	Local effects	m a /m 3	
Concentration	147	mg/m³	
Type of value	Derived No Effect Level (DNEL)		
Reference group	Worker		
Duration of exposure	Long term		
Route of exposure Mode of action	dermal		
Concentration	Systemic effects 125	mg/kg	
Type of value	Derived No Effect Level (DNEL)		
Reference group	Worker		
Duration of exposure	Long term		
Route of exposure Mode of action	inhalative Systemic effects		
Concentration	98	mg/m³	
Type of value	Derived No Effect Level (DNEL)		
Reference group	Consumer		
Duration of exposure	Acute		
Route of exposure	dermal		
Mode of action	Systemic effects		
Concentration	89,5	mg/kg	

Frade name: Marabu do it Satin Matt 0	173 150 ml	Ň
	Version: 4/GB	Marabu Date revised: 09.07.2019
Substance number: 21070006073	Replaces Version: 3 / GB	Print date: 13.07.19
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Acute	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	426	mg/m³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Acute	
Route of exposure Mode of action	oral	
Concentration	Systemic effects 26,7	malka
Concentration	20,7	mg/kg
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Acute	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	147	mg/kg
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action Concentration	Systemic effects 75	mg/kg
T		
Type of value	Derived No Effect Level (DNEL) Consumer	
Reference group Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	59	mg/m³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	oral	
Mode of action	Systemic effects	_
Concentration	6,3	mg/kg
n-Butyl acetate		
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action Concentration	Systemic effects 960	mg/m³
	Derived No Effect Level (DNEL)	-
Type of value	Derived No Effect Level (DNEL) Worker	
Reference group Duration of exposure	Short term	
	inhalative	
Route of exposure		
Route of exposure Mode of action	Local effects	

Trade name: Marabu do it Satin Matt	t 073, 150 ml	ΔV
	Version: 4 / GB	Date revised: 09.07.2019
Substance number: 21070006073	Replaces Version: 3 / GB	Print date: 13.07.19
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action Concentration	Systemic effects 300	mg/m³
Type of value Reference group	Derived No Effect Level (DNEL) Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	480	mg/m³
Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	859,7	mg/m³
Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Short term	
Route of exposure Mode of action	inhalative Local effects	
Concentration	859,7	mg/m³
Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	· · · · · · · · · · · · · · · · · · ·
Concentration	102,34	mg/m³
Type of value	Derived No Effect Level (DNEL)	
Reference group	General Population	
Duration of exposure Route of exposure	Long term inhalative	
Mode of action	Local effects	
Concentration	102,34	mg/m³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	11	mg/kg/d
Predicted No Effect Conce	ntration (PNEC)	
Ethyl acetate		
Type of value	PNEC	
Type	Water	
Concentration	0,26	mg/l
Type of value	PNEC	

Safety data sheet in accordance with Trade name: Marabu do it Satin Matt 0		
	Version: 4 / GB	Date revised: 09.07.2019
Substance number: 21070006073	Replaces Version: 3 / GB	Print date: 13.07.19
Туре	Aquatic	
Concentration	0,026	mg/l
Type of value	PNEC	
Type Concentration	Freshwater sediment 0,34	mg/kg
Type of value	PNEC	
Type Concentration	Marine sediment 0,034	mg/kg
Type of value Type	PNEC Soil	
Concentration	0,22	mg/kg
2-Methoxy-1-methylethyl acet		
Reference substance Type of value	2-Methoxy-1-methylethyl acetate PNEC	
Type	Freshwater	
Concentration	0,635	mg/l
Type of value	PNEC	
Type Concentration	Freshwater sediment 3,29	mg/kg
Type of value	PNEC	
Туре	Soil	
Concentration Source	0,29 Literature value	mg/kg
Type of value	PNEC	
Type Concentration	Sewage treatment plant (STP) 100	~~~ <i>~</i> //
Source	Literature value	mg/l
Type of value	PNEC	
Туре	Marine sediment	
Concentration Source	0,329 Literature value	mg/kg
Type of value	PNEC	
Type	Saltwater	
Concentration	0,0635	mg/l
Propan-2-ol		
Type of value	PNEC Freshwater	
Type Concentration	140,9	mg/l
Type of value	PNEC	
Type Concentration	Saltwater 140,9	mg/l
	PNEC	U U
Type of value Type	Sewage treatment plant (STP)	
Concentration	2251	mg/l

Safety data sheet in accordance with	regulation (EC) No 1907/2006	
Trade name: Marabu do it Satin Matt 07	'3, 150 ml	
	Version: 4 / GB	Date revised: 09.07.2019
Substance number: 21070006073	Replaces Version: 3 / GB	Print date: 13.07.19
Type of value	PNEC	
Туре	Freshwater sediment	
Concentration	552	mg/kg
Type of value	PNEC	
Туре	Marine sediment	
Concentration	552	mg/kg
Type of value	PNEC	
Туре	Soil	
Concentration	28	mg/kg
2-Butoxyethanol		
Type of value	PNEC	
Туре	Freshwater	
Concentration	8,8	mg/l
Type of value	PNEC	
Туре	Soil	
Concentration	2,8	mg/kg
Type of value	PNEC	
Туре	Freshwater sediment	
Concentration	34,6	mg/kg
Type of value	PNEC	
Туре	Sewage treatment plant (STP)	
Concentration	463	mg/l
Type of value	PNEC	
Туре	Saltwater	
Concentration	0,88	mg/l
Type of value	PNEC	
Туре	Marine sediment	
Concentration	3,46	mg/kg
n-Butyl acetate		
Type of value	PNEC	
Туре	Freshwater	
Concentration	0,18	mg/l
Type of value	PNEC	
Туре	Saltwater	
Concentration	0,018	mg/l
Type of value	PNEC	
Туре	Freshwater sediment	
Concentration	0,981	mg/kg
Type of value	PNEC	
Туре	Marine sediment	
Concentration	0,0981	mg/kg
Type of value	PNEC	
Туре	Soil	
Concentration	0,0903	mg/kg

Trade name: Marabu do it Satin Matt 073, 150 ml

		Version: 4 / GB	Date revised: 09.07.2019
Substance number:	21070006073	Replaces Version: 3 / GB	Print date: 13.07.19

Type of value	PNEC	
Туре	Sewage treatment plant (STP)	
Concentration	35,6	mg/l
Type of value	PNEC	
Туре	Water (intermittent release)	
Concentration	0,36	mg/l

8.2. Exposure controls

Exposure controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Short term: filter apparatus, Filter A/P2; Self-contained breathing apparatus.

Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

For prolonged or repeated handling nitrile rubber gloves with textile undergloves are required.

Material thickness	>	0,5	mm
Breakthrough time	<	30	min

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

Eye protection

Safety glasses

Body protection

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Aerosol	
coloured	
solvent-like	
Not applicable	
not determined	
boiling range	
appr. 76	°C
1.013 hPa	
Literature value	
	coloured solvent-like Not applicable not determined boiling range appr. 76 1.013 hPa

Safety data sheet in accordance wit	h regulation (EC) No	0 1907/2	006	
Trade name: Marabu do it Satin Matt	073, 150 ml			
	Version: 4	/ GB		Date revised: 09.07.2019
Substance number: 21070006073	Replaces V	ersion:	3 / GB	Print date: 13.07.19
Remarks				
Upper/lower flammability o	Not applicable			
Lower explosion limit	appr. 1,5		%(V)	
Upper explosion limit	appr. 1,5 appr. 15		%(V) %(V)	
Source	Literature value			
Density				
Value	0,75		g/cm³	
Temperature	20	°C		
Solubility in water				
Remarks	immiscible			
Partition coefficient: n-octa				
Remarks	Not applicable			
Ignition temperature				
Value Source	appr. 420 Literature value		°C	
	Literature value			
Viscosity Remarks				
Remarks	not determined			
9.2. Other information				
Other information				
The physical specifications a	re approximate values	s and re	ier to the used salety	relevant component(s).
SECTION 10: Stability and	reactivity			
10.1. Reactivity				
None known				
10.2. Chemical stability Stable under recommended	storage and handling	conditio	ns (see section 7).	
10.3. Possibility of hazardous	s reactions			
Keep away from oxidising ag exothermic reactions.		and str	ongly acid materials i	n order to avoid
10.4. Conditions to avoid				
When exposed to high tempe and direct sunlight.	eratures may produce	hazardo	ous decomposition pro	oducts. Protect from heat
10.5. Incompatible materials None known				
	producto			
10.6. Hazardous decompositi See chapter 5.2 (Firefighting		azards	arising from the subst	ance or mixture).
SECTION 11: Toxicologic	al information			
11.1. Information on toxicolo	gical effects			
Acute inhalational toxicity	-			
Remarks	Based on available c	lata, the	classification criteria	are not met.
Skin corrosion/irritation				
Remarks	Based on available c	lata, the	classification criteria	are not met.
		,		

Serious eye damage/irritation

evaluation irritant

Trade name: Marabu do it Satin Matt 073, 150 ml

Substance number: 21070006073	Version: 4 / GB Replaces Version: 3 / GB	Date revised: 09.07.2019 Print date: 13.07.19
Remarks	The classification criteria are met.	
Sensitization		
Remarks	Based on available data, the classification crit	teria are not met.
Mutagenicity		
Remarks	Based on available data, the classification crit	teria are not met.
Reproductive toxicity		
Remarks	Based on available data, the classification crit	teria are not met.
Carcinogenicity		
Remarks	Based on available data, the classification crit	teria are not met.
Specific Target Organ To	xicity (STOT)	
Single exposure		
Remarks	The classification criteria are met.	
evaluation	May cause drowsiness or dizziness.	
Repeated exposure Remarks	Based on available data, the classification crit	teria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Experience in practice

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation. Ingestion may cause nausea, diarrhoea and vomiting.

Other information

There are no data available on the mixture itself.

The mixture has been assessed following the additivity method of the GHS/CLP Regulation (EC) No 1272/2008.

SECTION 12: Ecological information

12.1. Toxicity

General information

There are no data available on the mixture itself.Do not allow to enter drains or water courses.The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as dangerous for the environment.

12.2. Persistence and degradability

General information

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

Partition coefficient: n-octanol/water

Remarks

Not applicable

12.4. Mobility in soil

General information

There are no data available on the mixture itself.

Trade name: Marabu do it Satin Matt 073, 150 ml

Substance number: 21070006073

Version: 4 / GB Replaces Version: 3 / GB Date revised: 09.07.2019 Print date: 13.07.19

12.5. Results of PBT and vPvB assessment

General information

There are no data available on the mixture itself.

12.6. Other adverse effects

General information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations for the product

Do not allow to enter drains or water courses.

Disposal recommendations for packaging

Completely emptied packagings can be given for recycling. Not emptied containers are hazardous waste (waste code number 150110).

SECTION 14: Transport information

Land transport ADR/RID

 14.1. UN number UN 1950 14.2. UN proper shipping name AEROSOLS 14.3. Transport hazard class(es) Class 	2
Label 14.4. Packing group	2.1
Packing group Limited Quantity Transport category 14.5. Environmental hazards	- 1 I 2
- Tunnel restriction code	D
Marine transport IMDG/GGVSee 14.1. UN number UN 1950 14.2. UN proper shipping name AEROSOLS 14.3. Transport hazard class(es) Class 14.4. Packing group Packing group 14.5. Environmental hazards no	2.1
Air transport ICAO/IATA 14.1. UN number UN 1950 14.2. UN proper shipping name	
AEROSOLS 14.3. Transport hazard class(es) Class 14.4. Packing group	2.1



Safety data sheet in ac	cordance w	ith regulation (EC) No 1907	7/2006				
Trade name: Marabu do	o it Satin Mat					_		Marabu
Substance number: 21	070006073		: 4 / GB es Versior	n: 3/G	B	D	ate revised: Print dat	09.07.2019 e: 13.07.19
Packing group 14.5. Environmen -	ntal hazards	-						
	cautions for n the user's p ort in closed c	user				nt of an a	ccident or spil	lage.
Other information 14.7. Transport ir ^{no} SECTION 15: Re		ding to Annex II o information	f Marpol	and the	BC Cod	le		
15.1. Safety, health or mixture	n and envi	ronmental regu	ulations	/legisl	ation s	pecific	for the sul	ostance
Major-accident	-							
Category	8	Extremely flamm	able	10	0.000	kg	50.000	kg
VOC								
VOC (CH) VOC (EU)		83,6 83,6	% %	627 627	g/l g/l			
Other information	on							
The product do	es not contai	n substances of ve	ery high co	oncern (SVHC).			
15.2. Chemical saf For this prepara		sment ical safety assessm	nent has r	not been	carried c	out.		
SECTION 16: Oth	hor infor	mation						
Hazard stateme	ints listed i	•		-I				
H225 H226		Highly flammable Flammable liquic	•	-	Jr.			
H302		Harmful if swallo		our.				
H312		Harmful in conta		in.				
H315		Causes skin irrita	ation.					
H319		Causes serious e	eye irritati	on.				
H332		Harmful if inhaled						
H336		May cause drows	siness or	dizzines	SS.			
CLP categories	listed in C	•						
Acute Tox. 4		Acute toxicity, Ca						
Eye Irrit. 2		Eye irritation, Ca	• •					
Flam. Liq. 2 Flam. Liq. 3		Flammable liquic Flammable liquic						
Skin Irrit. 2		Skin irritation, Ca		yO				
STOT SE 3		Specific target or		ity - sing	gle expos	ure, Cate	egory 3	
Abbreviations								
RID: Règlemer GGVSee: Gefa IMDG: Internati ICAO: Internati	nt concernant hrgutverordn ional Maritim onal Air Tran	tif au transport inter le transport interna ung See e Code for Danger sport Association ation Organization	ational fer	roviaire				oute
CAS: Chemical								

Safety data sheet in accordance with regulation (EC) No 1907/2006 Trade name: Marabu do it Satin Matt 073, 150 ml Version: 4/GB Substance number: 21070006073 Replaces Version: 3 / GB EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances **EmS: Emergency Schedules** AICS: Australian Inventory of Chemical Substances MITI: Ministry of International Trade and Industry (Japan) TSCA: Toxic Substances Control Act (USA)

Date revised: 09.07.2019 Print date: 13.07.19

VOC: Volatile Organic Compound LD: Lethal dose LC: Lethal concentration SVHC: Substances of verv high concern DNEL: Derived no effect level PNEC: Predicted no effect concentration **UN: United Nations** OEL: Occupational exposure limit

Supplemental information

Relevant changes compared with the previous version of the safety data sheet are marked with: *** This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship. The information in this Safety Data Sheet is based on the present state of knowledge and current legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.