


Page 1/10

# Safety data sheet



Printing date 28.03.2017

Revision: 28.03.2017

Trade name: Aerosol Molotow Premium diverse Farben

	(Contd. of page 1)
· Hazard statements	
H222-H229 Extren	nely flammable aerosol. Pressurised container: May burst if heated.
H319 Cause	s serious eye irritation.
H336 May c	ause drowsiness or dizziness.
· Precautionary stat	ements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
	smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P305+P351+P338	3 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.
• Additional inform	
	entilation, explosive atmosphere/gas mix may be created.
Contains CAS 2222	716-38-3 Polyamide and fatty acid derivatives. May produce an allergic reaction.
$\cdot$ 2.3 Other hazards	

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB**: Not applicable.

×

# **SECTION 3: Composition/information on ingredients**

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

### · Dangerous components:

CAS: 67-64-1	acetone	25-<50%
EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	🚸 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2, H319; STOT SE 3, H336	5
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane 🚸 Flam. Gas 1, H220; 🔗 Press. Gas C, H280	10-<25%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane (containing ≤ 0,1 % butadiene (203-450-8))	5-<10%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-xxxx	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	5-<10%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate Tlam. Liq. 3, H226; (1) STOT SE 3, H336	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane (containing ≤ 0,1 % butadiene (203-450-8)) � Flam. Gas 1, H220; � Press. Gas C, H280	5-<10%

Printing date 28.03.2017

Revision: 28.03.2017

Trade name: Aerosol Molotow Premium diverse Farben

		ontd. of page
CAS: 9004-70-0	nitrocellulose with water(not less than 25% water, by mass)	2.5-<5%
	🤣 Unst. Expl., H200	
CAS: 1330-20-7	xylene	2.5-<5%
EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	Flam. Liq. 3, H226;  Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 64-17-5	ethanol	1-<2.5%
EINECS: 200-578-6	🚸 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2, H319	
CAS: 7397-62-8	butyl glycollate	<1%
EINECS: 230-991-7	🕹 Repr. 2, H361; 📀 Eye Dam. 1, H318	
CAS: 222716-38-3	CAS 222716-38-3 Polyamide and fatty acid derivatives	<1%
	STOT RE 2, H373; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

- 4.1 Description of first aid measures
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

# **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media -
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Cool container whit water
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures.
- · 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

# **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- Do not flush with water or aqueous cleansing agents
- 6.4 Reference to other sections
  See Section 7 for information on safe handling.
  See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Printing date 28.03.2017

Revision: 28.03.2017

Trade name: Aerosol Molotow Premium diverse Farben

(Contd. of page 3)

See Section 13 for disposal information.

# SECTION 7: Handling and storage

### · 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Take note of emission threshold.

Use only in well ventilated areas.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

*Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.* 

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• *Requirements to be met by storerooms and receptacles: Store in a cool location.* 

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- 7.3 Specific end use(s) No further relevant information available.

# SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

67-64-1 acetone

WEL Short-term value: 3620 mg/m<sup>3</sup>, 1500 ppm Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm

106-97-8 butane (containing ≤0,1 % butadiene (203-450-8))

WEL Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m<sup>3</sup>, 100 ppm Long-term value: 274 mg/m<sup>3</sup>, 50 ppm Sk

# 123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

1330-20-7 xylene

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm Long-term value: 220 mg/m<sup>3</sup>, 50 ppm

Sk; BMGV

# 64-17-5 ethanol

WEL Long-term value: 1920 mg/m<sup>3</sup>, 1000 ppm

(Contd. on page 5)

GB -

<i>inting date 28.03.2017</i>		Revision: 28.03.20
ade name: Aerosol Mol	otow Premium diverse Farben	
		(Contd. of page
· Ingredients with biold	gical limit values:	
1330-20-7 xylene		
BMGV 650 mmol/mo	creatinine	
Medium: urin		
Sampling time	: post shift	
	ethyl hippuric acid	
· Additional information	<b>n:</b> The lists valid during the making were us	sed as basis.
· 8.2 Exposure controls		
· Personal protective eq		
· General protective an		
	tuffs, beverages and feed.	
Immediately remove a	ll soiled and contaminated clothing	
	eaks and at the end of work.	
Do not inhale gases /	<sup>s</sup> umes / aerosols.	
Avoid contact with the		
Avoid contact with the		
· Respiratory protection		
	cing concentrations above the exposure	
	with combination filter, class A1P2 minimu	um, or breathing mask with outer air supp
• Protection of hands:		
	s to be impermeable and resistant to the pro	
	ve material on consideration of the pend	etration times, rates of diffusion and i
degradation		
• Material of gloves Nit		
· Penetration time of g		
	ed after every contamination.	
	h time has to be found out by the manufac	turer of the protective gloves and has to
observed.		
	contact of a maximum of 15 minutes glo	oves made of the following materials a
suitable:		
butyl rubber, 0,7mm		
• Eye protection:		
Tighthy see	led goggles	
1 ignity sed	κα ξυζζικο	
SECTION 9: Phy.	sical and chemical properties	
• 9.1 Information on be	usic physical and chemical properties	
· General Information	**	
· Appearance:		
Form:	Aerosol	
Colour:	According to product sp	pecification
· Odour:	Characteristic	-
· Odour threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
· Change in condition Melting point/freezi	ng point: Undetermined.	

(Contd. on page 6)

GB

Printing date 28.03.2017

Revision: 28.03.2017

	(Contd. of page :
Flash point:	<0 °C
-	Without propellant gas.
Flammability (solid, gas):	Not applicable.
Ignition temperature:	315 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	In use, may form flammable/explosive vapour-air mixture.
Explosion limits:	
Lower:	1.7 Vol %
Upper:	13.0 Vol %
Vapour pressure at 20 °C:	3600 hPa
Density:	Not determined.
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	77.7 %
	With propellant gas. Content given by weight.
VOC (EU)	77.67 %
Solids content:	22.2 %
9.2 Other information	No further relevant information available.

# **SECTION 10: Stability and reactivity**

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions Reacts with acids, alkalis and oxidising agents.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Possible in traces.

# **SECTION 11: Toxicological information**

· 11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- $\cdot$  Serious eye damage/irritation

Causes serious eye irritation.

(Contd. on page 7)

<sup>•</sup> Primary irritant effect:

GB -

Printing date 28.03.2017

Revision: 28.03.2017

Trade name: Aerosol Molotow Premium diverse Farben

(Contd. of page 6)

- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- $\cdot$  Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- **SECTION 12: Ecological information**
- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Ikke relevant.
- · 12.6 Other adverse effects No further relevant information available.

### **SECTION 13: Disposal considerations**

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

15 01 10\* packaging containing residues of or contaminated by hazardous substances

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number		
· ADR, IMDG, IATA	UN1950	
· 14.2 UN proper shipping name		
$\cdot ADR$	1950 AEROSOLS	
·IMDG	AEROSOLS	
·IATA	AEROSOLS, flammable	
· 14.3 Transport hazard class(es)		
·ADR		
2		

Printing date 28.03.2017

Revision: 28.03.2017

	erse Farben
	(Contd. of page
Label	2.1
IMDG, IATA	
Class	2.1
Label	2.1
14.4 Packing group	
ADR, IMDG, IATA	Void
	not classified
14.5 Environmental hazards:	N.
Marine pollutant:	No
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler):	-
EMS Number:	not classified F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
Segregation Code	Category A. For AEROSOLS with a capacity above 1 litre Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre Segregation as for class 9. Stow "separated from" class except for division 1.4. For AEROSOLS with a capacit above 1 litre: Segregation as for the appropriat subdivision of class 2. For WASTE AEROSOLS Segregation as for the appropriate subdivision of class 2.
14.7 Transport in bulk according to Ann Marpol and the IBC Code	<b>ex II of</b> Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
Transport category Tunnel restriction code	2 D
IMDG Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

# **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

\*

• Named dangerous substances - ANNEX I None of the ingredients is listed. • Seveso category P3a FLAMMABLE AEROSOLS

(Contd. on page 9)

GB

Printing date 28.03.2017

Revision: 28.03.2017

Trade name: Aerosol Molotow Premium diverse Farben

(Contd. of page 8)

- $\cdot$  Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t  $\cdot$  Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:

· Technical instructions (air):

Class	Share in %
NK	50-100

• Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H200 Unstable explosives. H220 Extremely flammable gas. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H280 Contains gas under pressure; may explode if heated. H302 Harmful if swallowed. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness. H361 Suspected of damaging fertility or the unborn child. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. · Department issuing SDS: Product safety department · Contact: Hr. Hamberger · Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Unst. Expl.: Explosives - Unstable explosive Flam. Gas 1: Flammable gases - Category 1 Aerosol 1: Aerosols - Category 1 Press. Gas C: Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Repr. 2: Reproductive toxicity - Category 2

GB

Printing date 28.03.2017

Revision: 28.03.2017

Trade name: Aerosol Molotow Premium diverse Farben

(Contd. of page 9)

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 • \* Data compared to the previous version altered.