Trade name: Marabu do it Satin Matt 052, 150 ml

Version: 4 / GB Date revised: 09.07.2019

Substance number: 21070006052 Replaces Version: 3 / GB Print date: 13.07.19

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Marabu do it Satin Matt 052, 150 ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/preparation

Colour spray

Identified Uses

SU21 Consumer uses: Private households (= general public = consumers)

PC9a Coatings and paints, thinners, paint removers

1.3. Details of the supplier of the safety data sheet

Address

Marabu GmbH & Co. KG Asperger Strasse 4 71732 Tamm Germany

Telephone no. +49-7141/691-0 Fax no. +49-7141/691-147

Information provided Department product safety

by / telephone

E-mail address of PR

PRSI@marabu.de

person responsible for this SDS

.........

1.4. Emergency telephone number

(+49) (0)621-60-43333

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)

Aerosol 1

H222

H229

Eye Irrit. 2 H319 STOT SE 3 H336

2.2. Label elements

Labelling according to regulation (EC) No 1272/2008

Hazard pictograms



Signal word

Danger

Hazard statements

H222 Extremely flammable aerosol.

Trade name: Marabu do it Satin Matt 052, 150 ml

Version: 4 / GB Date revised: 09.07.2019

Substance number: 21070006052 Replaces Version: 3 / GB Print date: 13.07.19

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.
P264.1 Wash hands thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

P501.9 Dispose of contents/container as problematic waste.

Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains Ethyl acetate;Propan-2-ol;n-Butyl acetate;2-Methoxy-1-methylethyl acetate

Supplemental information

EUH066 Repeated exposure may cause skin dryness or cracking.

Further supplemental information

Without adequate ventilation, explosive atmosphere/gas mix may be created.

2.3. Other hazards

No special hazards have to be mentioned.

SECTION 3: Composition/information on ingredients ***

3.2. Mixtures

Chemical characterization

Solvent based colour spray

Hazardous ingredients

Ethyl acetate

CAS No. 141-78-6 EINECS no. 205-500-4

Registration no. 01-2119475103-46

Concentration >= 10 < 20 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 2 H225 Eye Irrit. 2 H319 STOT SE 3 H336

Propan-2-ol

CAS No. 67-63-0 EINECS no. 200-661-7

Registration no. 01-2119457558-25

Concentration >= 10 < 20 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 2 H225 Eye Irrit. 2 H319

Trade name: Marabu do it Satin Matt 052, 150 ml

Version: 4 / GB Date revised: 09.07.2019

Substance number: 21070006052 Replaces Version: 3 / GB Print date: 13.07.19

STOT SE 3 H336

n-Butyl acetate

CAS No. 123-86-4 EINECS no. 204-658-1

Registration no. 01-2119485493-29

Concentration >= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3 H226 STOT SE 3 H336

2-Butoxyethanol

CAS No. 111-76-2 EINECS no. 203-905-0

Registration no. 01-2119475108-36

Concentration >= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)

 Skin Irrit. 2
 H315

 Acute Tox. 4
 H332

 Acute Tox. 4
 H312

 Acute Tox. 4
 H302

 Eye Irrit. 2
 H319

2-Methoxy-1-methylethyl acetate

CAS No. 108-65-6 EINECS no. 203-603-9

Registration no. 01-2119475791-29

Concentration >= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3 H226 STOT SE 3 H336

Further ingredients ***

Hydrocarbons, C3-4; Petroleum gas

CAS No. 68476-40-4 EINECS no. 270-681-9

Registration no. 01-2119486557-22

Concentration >= 25 < 50 % [3]

Classification (Regulation (EC) No. 1272/2008)

Flam. Gas 1 H220 Press. Gas H280

[3] Substance with occupational exposure limits

SECTION 4: First aid measures

4.1. Description of first aid measures

Trade name: Marabu do it Satin Matt 052, 150 ml

Version: 4 / GB Date revised: 09.07.2019

Substance number: 21070006052 Replaces Version: 3 / GB Print date: 13.07.19

General information

In all cases of doubt, or when symptoms persist, seek medical attention. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Summon a doctor immediately.

After skin contact

After contact with skin, wash immediately with plenty of water. Don't use solvents.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

Summon a doctor immediately. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Until now no symptoms known so far.

4.3. Indication of any immediate medical attention and special treatment needed Hints for the physician / treatment

Treat symptomatically

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Recommended: alcohol resistant foam, CO2, powders, water spray/mist, Not be used for safety reasons: water jet

5.2. Special hazards arising from the substance or mixture

In the event of fire the following can be released: Carbon monoxide (CO); Carbon dioxide (CO2); dense black smoke

5.3. Advice for firefighters

Special protective equipment for fire-fighting

In case of combustion use a suitable breathing apparatus.

Other information

Cool endangered containers with water spray jet. Collect contaminated fire-fighting water separately, must not be discharged into the drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away sources of ignition. Ensure adequate ventilation. Do not breathe gas/fumes/vapour/spray. Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4. Reference to other sections

Trade name: Marabu do it Satin Matt 052, 150 ml

Version: 4 / GB Date revised: 09.07.2019

Substance number: 21070006052 Replaces Version: 3 / GB Print date: 13.07.19

Refer to protective measures listed in Sections 7 and 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Provide good ventilation of working area (local exhaust ventilation if necessary). Handle and open container with care. Isolate from sources of heat, sparks and open flame. Avoid skin and eye contact. Smoking, eating and drinking shall be prohibited in application area. Comply with the health and safety at work laws.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge.

Classification of fires / temperature class / Ignition group / Dust explosion class

Classification of fires C (Flammable gases)

Temperature class T2

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in accordance with national regulation

Further information on storage conditions

Keep away from sources of ignition. Keep container in a cool, well-ventilated place. Observe label precautions.

7.3. Specific end use(s)

Colour spray

SECTION 8: Exposure controls/personal protection ***

8.1. Control parameters

Exposure limit values ***

Ethyl	acetate
-------	---------

List

List

Type	WEL		
Value		200	ppm(
Short term exposure limit		400	ppm(
Status: 2011			

EH40

EH40

EH40

2-Methoxy-1-methylethyl acetate

Type	WEL	_		
Value	274	mg/m³	50	ppm(V)
Short term exposure limit	548	mg/m³	100	ppm(V)
Skin resorption / sensibilisation	n: Sk;	Status: 2011		

Propan-2-ol

List

Type	WEL			
Value	999	mg/m³	400	ppm(V)
Short term exposure limit	1250	mg/m³	500	ppm(V)
Status: 2011				

2-Butoxyethanol

List	EH40		
Type	WEL		
Value		25	ppm(V)

Trade name: Marabu do it Satin Matt 052, 150 ml

Date revised: 09.07.2019 Version: 4 / GB

Print date: 13.07.19 Substance number: 21070006052 Replaces Version: 3 / GB

50 Short term exposure limit ppm(V)

Skin resorption / sensibilisation: Sk; Status: 2011

n-Butyl acetate

List EH40 Type WEL

Value 724 mg/m³ 150 ppm(V) Short term exposure limit 966 mg/m³ 200 ppm(V)

Status: 2011

Derived No/Minimal Effect Levels (DNEL/DMEL) ***

Hydrocarbons, C3-4; Petroleum gas

Type of value Derived Minimal Effect Level (DMEL)

Reference group Worker Duration of exposure Long term Route of exposure inhalative Mode of action Systemic effects

Concentration mg/m³ 2,21

Type of value Derived No Effect Level (DNEL)

Reference group Worker Duration of exposure Long term Route of exposure dermal

Systemic effects Mode of action

Concentration mg/kg/d 23,4

Type of value Derived Minimal Effect Level (DMEL)

Reference group Consumer Duration of exposure Long term Route of exposure inhalative Mode of action Systemic effects

Concentration 0,066 mg/m³

Ethyl acetate

Derived No Effect Level (DNEL) Type of value

Reference group Worker Duration of exposure Acute Route of exposure inhalative Concentration

mg/m³ 1468

Type of value Derived No Effect Level (DNEL)

Reference group Worker Duration of exposure Acute Route of exposure inhalative Mode of action Local effects

Concentration 1468 g/m³

Type of value Derived No Effect Level (DNEL)

Reference group Worker Route of exposure dermal

Mode of action Chronic effects

Concentration 63 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group Worker Route of exposure inhalative Mode of action Chronic effects

Concentration 734 mg/m³

Trade name: Marabu do it Satin Matt 052, 150 ml

Version: 4 / GB Date revised: 09.07.2019

Substance number: 21070006052 Replaces Version: 3 / GB Print date: 13.07.19

Type of value Derived No Effect Level (DNEL)

Reference group

Route of exposure

Mode of action

Worker

inhalative

Chronic effects

Concentration 734 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group
Route of exposure
Mode of action
Consentration
Consentra

Concentration 734 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group

Route of exposure

Mode of action

Concentration

Consumer
inhalative
Local effects

Concentration 734 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Consumer Route of exposure dermal

Mode of action Chronic effects

Concentration 37 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group
Route of exposure
Mode of action
Chronic effects

Concentration 367 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Consumer Route of exposure oral

Mode of action Chronic effects

Concentration 4,5 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Route of exposure inhalative
Mode of action Local effects
Concentration 367

Concentration 367 mg/m³

2-Methoxy-1-methylethyl acetate

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 796 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure inhalative
Mode of action Systemic effects

Concentration 275 mg/m³

Trade name: Marabu do it Satin Matt 052, 150 ml

Version: 4 / GB Date revised: 09.07.2019

Substance number: 21070006052 Replaces Version: 3 / GB Print date: 13.07.19

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects
Concentration 320

Concentration 320 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Long term

Route of exposure inhalative

Mode of action Systemic effects

Concentration 33 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group

Duration of exposure

Route of exposure

Mode of action

Consumer

Long term

inhalative

Local effects

Concentration 33 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Duration of exposure Long term
Route of exposure oral

Mode of action Systemic effects

Concentration 36 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group

Duration of exposure

Route of exposure

Mode of action

Concentration

Worker

Lifetime

inhalative

Local effects

Concentration 550 mg/m³

Propan-2-ol

Type of value Derived No Effect Level (DNEL)

Reference group

Duration of exposure

Route of exposure

Mode of action

Worker

Long term

inhalative

Systemic effects

Concentration 500 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 888 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group General Population

Duration of exposure Long term
Route of exposure inhalative
Mode of action Systemic effects

Concentration 89 mg/m³

Trade name: Marabu do it Satin Matt 052, 150 ml

Version: 4 / GB Date revised: 09.07.2019

Substance number: 21070006052 Replaces Version: 3 / GB Print date: 13.07.19

Type of value Derived No Effect Level (DNEL)

Reference group General Population

Duration of exposure Long term Route of exposure dermal

Mode of action Systemic effects

Concentration 319 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group General Population

Duration of exposure Long term Route of exposure oral

Mode of action Systemic effects

Concentration 26 mg/kg/d

2-Butoxyethanol

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Acute
Route of exposure dermal

Mode of action Systemic effects

Concentration 89 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group

Duration of exposure

Route of exposure

Mode of action

Worker

Short term

inhalative

Systemic effects

Concentration 1091 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group General Population

Duration of exposure
Route of exposure
Mode of action
Someontestion
Short term
inhalative
Local effects

Concentration 147 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 125 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group
Duration of exposure
Route of exposure
Mode of action
Worker
Long term
inhalative
Systemic effects

Concentration 98 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Duration of exposure Acute
Route of exposure dermal

Mode of action Systemic effects

Concentration 89,5 mg/kg

Trade name: Marabu do it Satin Matt 052, 150 ml

Version: 4 / GB Date revised: 09.07.2019

Substance number: 21070006052 Replaces Version: 3 / GB Print date: 13.07.19

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Acute

Route of exposure inhalative

Mode of action Systemic effects

Concentration 426 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Acute

Route of exposure oral

Mode of action Systemic effects

Concentration 26,7 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group

Duration of exposure

Route of exposure

Mode of action

Local effects

Concentration 147 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 75 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Long term

Route of exposure inhalative

Mode of action Systemic effects

Concentration 59 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Consumer
Duration of exposure Long term
Route of exposure oral

Mode of action Systemic effects

Concentration 6,3 mg/kg

n-Butyl acetate

Type of value Derived No Effect Level (DNEL)

Reference group
Duration of exposure
Route of exposure
Mode of action
Worker
Short term
inhalative
Systemic effects

Concentration 960 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Worker

Duration of exposure Short term

Route of exposure inhalative

Mode of action Local effects

Concentration 960 mg/m³

Trade name: Marabu do it Satin Matt 052, 150 ml

Version: 4 / GB Date revised: 09.07.2019

mg/m³

Substance number: 21070006052 Replaces Version: 3 / GB Print date: 13.07.19

Type of value Derived No Effect Level (DNEL)

Reference group

Duration of exposure

Route of exposure

Mode of action

Worker

Long term

inhalative

Systemic effects

Concentration 300 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group

Duration of exposure

Route of exposure

Mode of action

Concentration

Worker

Long term

inhalative

Local effects

480

Type of value Derived No Effect Level (DNEL)

Reference group General Population

Duration of exposure
Route of exposure
Mode of action
Systemic effects
Systemic effects

Concentration 859,7 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group General Population

Duration of exposure

Route of exposure

Mode of action

Concentration

Short term
inhalative
Local effects

Concentration 859,7 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group General Population

Duration of exposure
Route of exposure
Mode of action
Systemic effects
Concentration

Long term
inhalative
Systemic effects

Concentration 102,34 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group General Population

Duration of exposure
Route of exposure
Mode of action
Concentration
Long term
inhalative
Local effects
102.34

Concentration 102,34 mg/m³

Type of value Derived No Effect Level (DNEL)

Reference group Worker
Duration of exposure Long term
Route of exposure dermal

Mode of action Systemic effects

Concentration 11 mg/kg/d

Predicted No Effect Concentration (PNEC)

Ethyl acetate

Type of value PNEC Type Water

Concentration 0,26 mg/l

Type of value PNEC

Trade name: Marabu do it Satin Matt 052, 150 ml

Version: 4 / GB Date revised: 09.07.2019

Substance number: 21070006052 Replaces Version: 3 / GB Print date: 13.07.19

Type Aquatic

Concentration 0,026 mg/l

Type of value PNEC

Type Freshwater sediment

Concentration 0,34 mg/kg

Type of value PNEC

Type Marine sediment

Concentration 0,034 mg/kg

Type of value PNEC Type Soil

Concentration 0,22 mg/kg

2-Methoxy-1-methylethyl acetate

Reference substance 2-Methoxy-1-methylethyl acetate

Type of value PNEC
Type Freshwater
Concentration 0.635

Concentration 0,635 mg/l

Type of value PNEC

Type Freshwater sediment

Concentration 3,29 mg/kg

Type of value PNEC Type Soil

Concentration 0,29 mg/kg

Source Literature value

Type of value PNEC

Type Sewage treatment plant (STP)

Concentration 100 mg/l

Source Literature value

Type of value PNEC

Type Marine sediment

Concentration 0,329 mg/kg

Source Literature value

Type of value PNEC
Type Saltwater

Concentration 0,0635 mg/l

Propan-2-ol

Type of value PNEC
Type Freshwater

Concentration 140,9 mg/l

Type of value PNEC Type Saltwater

Concentration 140,9 mg/l

Type of value PNEC

Type Sewage treatment plant (STP)

Concentration 2251 mg/l

Trade name: Marabu do it Satin Matt 052, 150 ml

Version: 4/GB Date revised: 09.07.2019

Print date: 13.07.19 Substance number: 21070006052 Replaces Version: 3 / GB

Type of value **PNEC**

Type Freshwater sediment

Concentration 552 mg/kg

Type of value **PNEC**

Marine sediment Type

Concentration 552 mg/kg

PNEC Type of value Type Soil

Concentration 28 mg/kg

2-Butoxyethanol

PNEC Type of value Type Freshwater

Concentration mg/l 8.8

PNEC Type of value Type Soil

Concentration 2,8 mg/kg

Type of value **PNEC**

Freshwater sediment Type

Concentration 34,6 mg/kg

PNEC Type of value

Sewage treatment plant (STP) Type

Concentration mg/l

Type of value **PNEC** Type Saltwater

Concentration 0,88 mg/l

PNEC Type of value

Type Marine sediment

Concentration 3,46 mg/kg

n-Butyl acetate

Type of value **PNEC** Type Freshwater

Concentration 0,18 mg/l

PNEC Type of value Type Saltwater

Concentration 0,018 mg/l

PNEC Type of value

Type Freshwater sediment

Concentration 0,981 mg/kg

PNEC Type of value

Type Marine sediment

Concentration 0,0981 mg/kg

PNEC Type of value Soil Type

0,0903 Concentration mg/kg

Trade name: Marabu do it Satin Matt 052, 150 ml

Version: 4 / GB Date revised: 09.07.2019

Substance number: 21070006052 Replaces Version: 3 / GB Print date: 13.07.19

Type of value PNEC

Type Sewage treatment plant (STP)

Concentration 35,6 mg/l

Type of value PNEC

Type Water (intermittent release)

Concentration 0,36 mg/l

8.2. Exposure controls

Exposure controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Short term: filter apparatus, Filter A/P2; Self-contained breathing apparatus.

Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

For prolonged or repeated handling nitrile rubber gloves with textile undergloves are required.

Material thickness > 0,5 mm Breakthrough time < 30 min

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

Eye protection

Safety glasses

Body protection

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form Aerosol
Colour coloured
Odour solvent-like

pH value

Remarks Not applicable

Melting point

Remarks not determined

Initial boiling point and boiling range

Value appr. 76 °C

Pressure 1.013 hPa

Source Literature value

Flash point

Trade name: Marabu do it Satin Matt 052, 150 ml

Version: 4 / GB Date revised: 09.07.2019

Substance number: 21070006052 Replaces Version: 3 / GB Print date: 13.07.19

Remarks Not applicable

Upper/lower flammability or explosive limits

Lower explosion limit appr. 1,5 %(V)
Upper explosion limit appr. 15 %(V)

Source Literature value

Density

Value 0,75 g/cm³

Temperature 20 °C

Solubility in water

Remarks immiscible

Partition coefficient: n-octanol/water

Remarks Not applicable

Ignition temperature

Value appr. 420 °C

Source Literature value

Viscosity

Remarks

Remarks not determined

9.2. Other information

Other information

The physical specifications are approximate values and refer to the used safety relevant component(s).

SECTION 10: Stability and reactivity

10.1. Reactivity

None known

10.2. Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3. Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4. Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products. Protect from heat and direct sunlight.

10.5. Incompatible materials

None known

10.6. Hazardous decomposition products

See chapter 5.2 (Firefighting measures - Special hazards arising from the substance or mixture).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute inhalational toxicity

Remarks Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Remarks Based on available data, the classification criteria are not met.

Serious eye damage/irritation

evaluation irritant

Trade name: Marabu do it Satin Matt 052, 150 ml

Version: 4 / GB Date revised: 09.07.2019

Substance number: 21070006052 Replaces Version: 3 / GB Print date: 13.07.19

Remarks The classification criteria are met.

Sensitization

Remarks Based on available data, the classification criteria are not met.

Mutagenicity

Remarks Based on available data, the classification criteria are not met.

Reproductive toxicity

Remarks Based on available data, the classification criteria are not met.

Carcinogenicity

Remarks Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity (STOT)

Single exposure

Remarks The classification criteria are met. evaluation May cause drowsiness or dizziness.

Repeated exposure

Remarks Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Experience in practice

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation. Ingestion may cause nausea, diarrhoea and vomiting.

Other information

There are no data available on the mixture itself.

The mixture has been assessed following the additivity method of the GHS/CLP Regulation (EC) No 1272/2008.

SECTION 12: Ecological information

12.1. Toxicity

General information

There are no data available on the mixture itself.Do not allow to enter drains or water courses.The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as dangerous for the environment.

12.2. Persistence and degradability

General information

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

Partition coefficient: n-octanol/water

Remarks Not applicable

12.4. Mobility in soil

General information

There are no data available on the mixture itself.

Trade name: Marabu do it Satin Matt 052, 150 ml

Version: 4 / GB Date revised: 09.07.2019

Substance number: 21070006052 Replaces Version: 3 / GB Print date: 13.07.19

12.5. Results of PBT and vPvB assessment

General information

There are no data available on the mixture itself.

12.6. Other adverse effects

General information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations for the product

Do not allow to enter drains or water courses.

Disposal recommendations for packaging

Completely emptied packagings can be given for recycling.

Not emptied containers are hazardous waste (waste code number 150110).

SECTION 14: Transport information

Land transport ADR/RID

14.1. **UN** number

UN 1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

Class 2 Label 2.1

14.4. Packing group

Packing group Limited Quantity 1 I
Transport category 2

14.5. Environmental hazards

-

Tunnel restriction code D

Marine transport IMDG/GGVSee

14.1. UN number

UN 1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

Class 2.1

14.4. Packing group

Packing group -

14.5. Environmental hazards

no

Air transport ICAO/IATA

14.1. UN number

UN 1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

Class 2.1

14.4. Packing group

Trade name: Marabu do it Satin Matt 052, 150 ml

Version: 4 / GB Date revised: 09.07.2019

Substance number: 21070006052 Replaces Version: 3 / GB Print date: 13.07.19

Packing group

14.5. Environmental hazards

-

Information for all modes of transport

14.6. Special precautions for user

Transport within the user's premises:

Always transport in closed containers that are upright and secure.

Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Other information

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

no

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Major-accident categories acc. 96/82/EC

Category	8	Extremely flammat	ole	10	.000	kg	50.000	kg
VOC								
VOC (CH)		83,6	%	627	g/l			
VOC (EU)		83,6	%	627	g/l			

Other information

The product does not contain substances of very high concern (SVHC).

15.2. Chemical safety assessment

For this preparation a chemical safety assessment has not been carried out.

SECTION 16: Other information

Hazard statements listed in Chapter 3

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness

CLP categories listed in Chapter 3

Acute Tox. 4	Acute toxicity, Category 4
Eye Irrit. 2	Eye irritation, Category 2
Flam. Liq. 2	Flammable liquid, Category 2
Flam. Liq. 3	Flammable liquid, Category 3
Skin Irrit. 2	Skin irritation, Category 2

STOT SE 3 Specific target organ toxicity - single exposure, Category 3

Abbreviations

ADR: Accord européen relatif au transport international des marchandises Dangereuses par Route RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses

GGVSee: Gefahrgutverordnung See

IMDG: International Maritime Code for Dangerous Goods

ICAO: International Air Transport Association IATA: International Civil Aviation Organization

CAS: Chemical Abstracts Service

Trade name: Marabu do it Satin Matt 052, 150 ml

Version: 4 / GB Date revised: 09.07.2019

Substance number: 21070006052 Replaces Version: 3 / GB Print date: 13.07.19

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

EmS: Emergency Schedules

AICS: Australian Inventory of Chemical Substances MITI: Ministry of International Trade and Industry (Japan)

TSCA: Toxic Substances Control Act (USA)

VOC: Volatile Organic Compound

LD: Lethal dose

LC: Lethal concentration

SVHC: Substances of very high concern

DNEL: Derived no effect level

PNEC: Predicted no effect concentration

UN: United Nations

OEL: Occupational exposure limit

Supplemental information

Relevant changes compared with the previous version of the safety data sheet are marked with: *** This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship. The information in this Safety Data Sheet is based on the present state of knowledge and current legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.