

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Revision date: 12/11/2021 Supersedes version of: 14/02/2017 Version: 5.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : WINSOR & NEWTON GENERAL PURPOSE MATT VARNISH SPRAY

Vaporizer : aerosol
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public

Industrial/Professional use spec : Industrial

For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

COLART EUROPE SAS SAS

5 rue René Panhard 72021 Le Mans Cedex 2

72021 LeMans

France

T +44 208 424 3270

r.enquiries@colart.co.uk

Distributor

COLART UK LTD

Goldthorn Road

DY11 7JN Kidderminster – Worcestershire

United Kingdom

T +44 (0) 2084243200

r.enquiries@colart.co.uk

Distributor

JASCO

1-5 Commercial Road Kingsgrove

+61- NSW 2208 New South Wales

T 029807 1555

Other

Colart International Holdings LTD

The MediaWorks Building

191 Wood Lane

GB-W12 7FP London - London

United Kingdom T 02084243200

r.enquiries@colart.co.uk

Distributor

Jasco Pty (NZ) Limited

5 Airpark Drive, Airport Oaks, Auckland Airport Auckland

P.O. Box 107010

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Australia	NSW Poisons Information Centre The Children's Hospital at Westmead	Locked Bag 4001 NSW 2145 Westmead	13 11 26	
New Zealand	New Zealand National Poison Centre Dunedin School of Medicine, University of Otago	PO Box 56 Dunedin 9054	0800 764 766 (0800 POISON)	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Skin corrosion/irritation, Category 2 H315
Specific target organ toxicity — Repeated exposure, Category 1 H372
Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :









GHS02

GHS07

GHS08 GHS09

Signal word (CLP) : Danger

Contains : STODDARD SOLVENT

Hazard statements (CLP) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H315 - Causes skin irritation.

H372 - Causes damage to organs through prolonged or repeated exposure.

H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) : P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, open flames, sparks. — No smoking.

P211 - Do not spray on an open flame or other ignition source.
P251 - Pressurized container: Do not pierce or burn, even after use.

P261 - Avoid breathing vapours, spray.

P271 - Use only outdoors or in a well-ventilated area.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

EUH-statements : EUH066 - Repeated exposure may cause skin dryness or cracking.

Child-resistant fastening : Applicable Tactile warning : Applicable

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Naphtha (petroleum), hydrotreated light	CAS-No.: 64742-49-0 EC-No.: 265-151-9	10 – 30	Flam. Liq. 2, H225 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
MEK (METHYL ETHYL KETONE), BUTANONE	CAS-No.: 78-93-3 EC-No.: 201-159-0	10 – 30	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
STODDARD SOLVENT	CAS-No.: 8052-41-3 EC-No.: 232-489-3	10 – 30	Flam. Liq. 3, H226 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Solvent naphtha (petroleum), light aliph.	CAS-No.: 64742-89-8 EC-No.: 265-192-2	5 – 10	Asp. Tox. 1, H304
HYDROCARBONS, C10-C12, ISOALKANES, <2% AROMATICS	CAS-No.: 90622-57-4 EC-No.: 923-037-2	5 – 10	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Xylene substance with a Community workplace exposure limit	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216- 32	1-3	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Asp. Tox. 1, H304 STOT SE 3, H335 Eye Irrit. 2, H319 Aquatic Chronic 3, H412
Isobutyl methacrylate	CAS-No.: 97-86-9 EC-No.: 202-613-0	1 – 3	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335
Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclics, <2% aromatics	CAS-No.: 64742-47-8 EC-No.: 265-149-8 REACH-no: 01-2119456620- 43	1 – 3	Flam. Liq. 3, H226 Asp. Tox. 1, H304
Toluene	CAS-No.: 108-88-3 EC-No.: 203-625-9	0.1 – 1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Cough. Remove person to fresh air and keep comfortable for breathing. Call a POISON

CENTER/doctor if you feel unwell.

First-aid measures after skin contact : Wash with plenty of water/.... Wash contaminated clothing before reuse. If skin irritation

occurs: Get medical advice/attention. Specific treatment (see supplemental first aid instruction on this label). Repeated exposure may cause skin dryness or cracking.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Direct contact with the eyes is likely to be

irritating. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Shortness of breath. May cause respiratory irritation.

12/11/2021 (Revision date) GB - en 3/15

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of

burns and injuries.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire fighting water from entering the environment. DO NOT fight fire

when fire reaches explosives. Evacuate area.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : No open flames. No smoking. Isolate from fire, if possible, without unnecessary risk.

Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible.

Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Hazardous waste due to potential risk of explosion. Do not pierce or burn, even after use. Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or

: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Do not spray on an open flame or other ignition source. Avoid

breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area.

Hygiene measures : Wash hands, forearms and face thoroughly after handling.

12/11/2021 (Revision date) GB - en 4/15

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Do not expose

to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Keep container tightly

closed.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Xylene (1330-20-7)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Xylene, mixed isomers, pure	
IOEL TWA [ppm]	50 ppm	
IOEL STEL	442 mg/m³	
IOEL STEL [ppm]	100 ppm	
Remark	Skin	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
France - Occupational Exposure Limits	·	
Local name	Xylène: mélange d'isomères	
VME (OEL TWA)	221 mg/m³	
VME (OEL TWA) [ppm]	50 ppm	
VLE (OEL C/STEL)	442 mg/m³	
VLE (OEL C/STEL) [ppm]	100 ppm	
Remark	Valeurs règlementaires contraignantes; risque de pénétration percutanée	
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487)	
Germany - Occupational Exposure Limits (TRGS 900)		
Local name	Xylol (alle Isomeren)	
AGW (OEL TWA) [1]	220 mg/m³	
AGW (OEL TWA) [2]	50 ppm	
Peak exposure limitation factor	2(II)	
Remark	DFG;EU;H	
Regulatory reference	TRGS900	
Germany - Biological limit values (TRGS 903)		
Local name	Xylol (alle Isomere)	
Biological limit value	2000 mg/l Parameter: Methylhippur-(Tolur-) säure (alle Isomere) - Untersuchungsmaterial: U = Urin - Probenahmezeitpunkt: b) Expositionsende, bzw. Schichtende - Festlegung/Begründung: 11/2016 DFG	
Regulatory reference	TRGS 903	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Xylene (1330-20-7)		
United Kingdom / Australia / New Zealand - Occupational Exposure Limits		
Local name	Xylene	
WEL TWA (OEL TWA) [1]	220 mg/m³ o-,m-,p- or mixed isomers	
WEL TWA (OEL TWA) [2]	50 ppm o-,m-,p- or mixed isomers	
WEL STEL (OEL STEL)	441 mg/m³ o-,m-,p- or mixed isomers	
WEL STEL (OEL STEL) [ppm]	100 ppm o-,m-,p- or mixed isomers	
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
United Kingdom / Australia / New Zealand - Biological limit values		
Local name	Xylene, o-, m-, p- or mixed isomers	
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift	
Regulatory reference EH40/2005 (Fourth edition, 2020). HSE		

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Wear protective gloves.

8.2.2.3. Respiratory protection

Respiratory protection:

Wear appropriate mask

8.2.2.4. Thermal hazards

No additional information available

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

8.2.3. Environmental exposure controls

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

: Liquid Physical state Colour Colourless. Appearance Liquid. Odour characteristic. Not available Odour threshold Melting point Not available Freezing point Not available **Boiling point** Not available

Flammability : Non flammable, Extremely flammable aerosol.

Explosive limits : Not available
Lower explosive limit (LEL) : Not available
Upper explosive limit (UEL) : Not available
Flash point : 41 °C
Auto-ignition temperature : > 250 °C
Decomposition temperature : Not available
pH : Not available

Viscosity, kinematic : ≈ 134000000 mm²/s

Solubility : Not available Partition coefficient n-octanol/water (Log Kow) : Not available Vapour pressure : Not available Vapour pressure at 50 °C : Not available : Not available Density Relative density : Not available Relative vapour density at 20 °C : Not available Particle size : Not applicable Particle size distribution : Not applicable Particle shape : Not applicable : Not applicable Particle aspect ratio Particle aggregation state : Not applicable : Not applicable Particle agglomeration state Particle specific surface area : Not applicable Particle dustiness : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 99.663944171076132525975

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

Not established.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Toluene (108-88-3)			
LD50 oral rat	5580 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EU Method B.1 (Acute Toxicity (Oral)), 95% CL: 5300 - 5910		
LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit, Animal sex: male, 95% CL: 9,63 - 20,77		
Isobutyl methacrylate (97-86-9)			
LD50 oral rat	9590 mg/kg bodyweight Animal: rat, Guideline: other:"Appraisal of the safety of chemicals in foods, drugs and cosmetics," by the Staff of the Division of Pharmacology, FDA, (1959)		
Xylene (1330-20-7)			
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male		
Solvent naphtha (petroleum), light aliph. (64742-89-8)			
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)		
Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-47-8)			
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.1175 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)		
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)		
LC50 Inhalation - Rat	> 5.28 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), 95% CL: 0,42 -		

Naphtha (petroleum), hydrotreated light (64742-49-0)

LD50 dermal rabbit > 5000 mg/kg bodyweight Animal: rabbit, Animal sex: male, 95% CL: 9,63 - 20,77	
---	--

Skin corrosion/irritation : Causes skin irritation.

Additional information : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/irritation : Not classified Respiratory or skin sensitisation : Not classified

Additional information : Based on available data, the classification criteria are not met

Germ cell mutagenicity : Not classified

Additional information : Based on available data, the classification criteria are not met

Carcinogenicity : Not classified

Additional information : Based on available data, the classification criteria are not met

Reproductive toxicity : Not classified

Additional information : Based on available data, the classification criteria are not met

12/11/2021 (Revision date) GB - en 8/15

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-47-8)			
NOAEL (animal/male, F0/P)	≥ 3000 mg/kg bodyweight Animal: rat, Animal sex: male		
STOT-single exposure :	Not classified		
Isobutyl methacrylate (97-86-9)			
STOT-single exposure	May cause respiratory irritation.		
Xylene (1330-20-7)			
STOT-single exposure	May cause respiratory irritation.		
MEK (METHYL ETHYL KETONE), BUTANONE	(78-93-3)		
STOT-single exposure	May cause drowsiness or dizziness.		
Naphtha (petroleum), hydrotreated light (6474	2-49-0)		
STOT-single exposure	May cause respiratory irritation.		
STOT-repeated exposure : Additional information :	Causes damage to organs through prolonged or repeated exposure. Based on available data, the classification criteria are not met		
Toluene (108-88-3)			
LOAEL (oral, rat, 90 days)	1250 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)		
NOAEL (oral, rat, 90 days)	625 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)		
NOAEC (inhalation, rat, vapour, 90 days)	2.355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study)		
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.		
Isobutyl methacrylate (97-86-9)			
LOAEC (inhalation, rat, gas, 90 days)	952 ppm Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)		
NOAEL (oral, rat, 90 days)	120 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity in Rodents)		
Xylene (1330-20-7)			
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)		
Hydrocarbons, C11-14, n-alkanes, isoalkanes,	, cyclics, <2% aromatics (64742-47-8)		
NOAEL (oral, rat, 90 days)	750 mg/kg bodyweight Animal: rat, Animal sex: female		
NOAEC (inhalation, rat, vapour, 90 days)	≥ 0.024 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)		
Naphtha (petroleum), hydrotreated light (64742-49-0)			
LOAEC (inhalation, rat, vapour, 90 days)	4.71 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study)		
NOAEC (inhalation, rat, vapour, 90 days)	2.355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study)		
STODDARD SOLVENT (8052-41-3)			
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.		
Aspiration hazard : Additional information :	Not classified Based on available data, the classification criteria are not met		

12/11/2021 (Revision date) GB - en 9/15

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

WINSOR & NEWTON GENERAL PURPOSE MATT VARNISH SPRAY	
Vaporizer	aerosol
Viscosity, kinematic	≈ 134000000 mm²/s

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Potential adverse human health effects and symptoms

: Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term : Not classified

(acute)

Hazardous to the aquatic environment, long-term : Toxic to aquatic life with long lasting effects.

(chronic)

(CHOTIC)			
Toluene (108-88-3)			
LC50 - Fish [1]	5.5 mg/l Test organisms (species): Oncorhynchus kisutch		
LOEC (chronic)	2.76 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'		
NOEC (chronic)	0.74 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'		
NOEC chronic fish	1.39 mg/l Test organisms (species): Oncorhynchus kisutch Duration: '40 d'		
Isobutyl methacrylate (97-86-9)			
LC50 - Fish [1]	20 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)		
EC50 - Crustacea [1]	> 29 mg/l Test organisms (species): Daphnia magna		
EC50 96h - Algae [1]	14 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)		
Xylene (1330-20-7)			
LC50 - Fish [1]	2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)		
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia		
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'		
MEK (METHYL ETHYL KETONE), BUTANONE (78-93-3)			
LC50 - Fish [1]	2993 mg/l Test organisms (species): Pimephales promelas		
EC50 - Crustacea [1]	308 mg/l Test organisms (species): Daphnia magna		
EC50 72h - Algae [1]	1972 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)		
EC50 96h - Algae [1]	2029 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)		

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Naphtha (petroleum), hydrotreated light (64742-49-0)		
LC50 - Fish [1]	8.41 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)	
EC50 - Crustacea [1]	4.7 mg/l Test organisms (species): Daphnia magna	
EC50 72h - Algae [1]	12.4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
EC50 72h - Algae [2]	18.9 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	

12.2. Persistence and degradability

WINSOR & NEWTON GENERAL PURPOSE MATT VARNISH SPRAY	
Persistence and degradability	May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

WINSOR & NEWTON GENERAL PURPOSE MATT VARNISH SPRAY	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use. Dispose of contents/container to hazardous or

special waste collection point, in accordance with local, regional, national and/or

international regulation.

Additional information : Flammable vapours may accumulate in the container.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN
14.1. UN number or ID number			
UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name			
Not applicable	AEROSOLS	Aerosols, flammable	Not applicable

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN
Transport document description			
UN 1950, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONMENTALL Y HAZARDOUS	UN 1950 Aerosols, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 , ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(e	es)		
Not applicable	2.1	2.1	Not applicable
¥	2	2	¥2
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available			

14.6. Special precautions for user

Overland transport

No data available

Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Packing instructions (IMDG) : P207, LP200
Special packing provisions (IMDG) : PP87, L2
EmS-No. (Fire) : F-D
EmS-No. (Spillage) : S-U
Stowage category (IMDG) : None
Stowage and handling (IMDG) : SW1, SW22
Segregation (IMDG) : SG69

Air transport

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

Inland waterway transport

No data available

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

15.1.2. National regulations

France

Storage class (LK)

CH - VOC (SR 814.018)

Occupational diseases		
Code	Description	
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them	
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide	
Germany		
Water hazard class (WGK	()	: WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)
Hazardous Incident Ordina	ance (12. BlmSchV)	: Is not subject of the Hazardous Incident Ordinance (12. BImSchV)
Netherlands		
SZW-lijst van kankerverwekkende stoffen		: Solvent naphtha (petroleum), light aliph.,Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclics, <2% aromatics,STODDARD SOLVENT,Naphtha (petroleum), hydrotreated light are listed
SZW-lijst van mutagene stoffen		: Solvent naphtha (petroleum), light aliph.,Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclics, <2% aromatics,STODDARD SOLVENT,Naphtha (petroleum), hydrotreated light are listed
SZW-lijst van reprotoxisch	e stoffen – Borstvoeding	: None of the components are listed
SZW-lijst van reprotoxisch	ie stoffen –	: None of the components are listed
Vruchtbaarheid		
SZW-lijst van reprotoxisch	e stoffen – Ontwikkeling	: Toluene,Xylene are listed
Denmark		
Class for fire hazard		: Class II-1
Store unit		: 5 liter
Classification remarks		: R10 <h222;h229;h315;h372;h411>; Emergency management guidelines for the storage of</h222;h229;h315;h372;h411>
		flammable liquids must be followed
Danish National Regulation	ns	 Young people below the age of 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with the product
		The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal
Switzerland		

12/11/2021 (Revision date) GB - en 13/15

: LK 2 - Liquefied or pressurized gases

: 43.71214738296656 %

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

United Kingdom / Australia / New Zealand

Other information

: This SDS is prepared in accordance with the model Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals.

Please read instructions / label before using product.

EMERGENCY CONTACTS

Jasco Pty Ltd : 02 9807 1555

Police and Fire Brigade : 000
Poisons information centre : 13 11 26
Safety Data Sheet applicable regions : Australia

This SDS is prepared in accordance with the model Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals. Supplied as permitted by New Zealand regulations; EPA Hazardous Substances (Safety Data Sheet) notice.

Please read instructions / label before using product.

EMERGENCY CONTACTS

Jasco Pty Ltd : 02 9807 1555

Poisons information centre : 0800 764 766 (0800 POISON)

Safety Data Sheet applicable regions : New Zealand.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE

COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and

amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-statements:		
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4	
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2	
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3	
Asp. Tox. 1	Aspiration hazard, Category 1	
EUH066	Repeated exposure may cause skin dryness or cracking.	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Liq. 2	Flammable liquids, Category 2	
Flam. Liq. 3	Flammable liquids, Category 3	
H222	Extremely flammable aerosol.	
H225	Highly flammable liquid and vapour.	
H226	Flammable liquid and vapour.	
H229	Pressurised container: May burst if heated.	
H304	May be fatal if swallowed and enters airways.	
H312	Harmful in contact with skin.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	

12/11/2021 (Revision date) GB - en 14/15

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Full text of H- and EUH-statements:		
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	
H336	May cause drowsiness or dizziness.	
H361	Suspected of damaging fertility or the unborn child.	
H372	Causes damage to organs through prolonged or repeated exposure.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
Repr. 2	Reproductive toxicity, Category 2	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
Skin Sens. 1	Skin sensitisation, Category 1	
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1	
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2	
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Aerosol 1	H222;H229	Expert judgment
Skin Irrit. 2	H315	Expert judgment
STOT RE 1	H372	Expert judgment
Aquatic Chronic 2	H411	Expert judgment

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.