

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Revision date: 10/11/2021 Supersedes version of: 23/11/2015 Version: 6.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : WINSOR & NEWTON PROFESSIONAL GLOSS VARNISH SPRAY

Vaporizer : aerosol Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public

Industrial/Professional use spec : Industrial

For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

COLART EUROPE SAS SAS

5 rue René Panhard 72021 Le Mans Cedex 2

72021 LeMans

France

T +44 208 424 3270

r.enquiries@colart.co.uk

Distributor

COLART UK LTD Goldthorn Road

DY11 7JN Kidderminster - Worcestershire

United Kingdom

T +44 (0) 2084243200

r.enquiries@colart.co.uk

Distributor

JASCO

1-5 Commercial Road Kingsgrove

+61- NSW 2208 New South Wales

T 029807 1555

Other

Colart International Holdings LTD

The MediaWorks Building

191 Wood Lane

GB- W12 7FP London - London

United Kingdom T 02084243200

r.enquiries@colart.co.uk

Distributor

Jasco Pty (NZ) Limited

5 Airpark Drive, Airport Oaks, Auckland Airport Auckland

P.O. Box 107010

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Australia	NSW Poisons Information Centre The Children's Hospital at Westmead	Locked Bag 4001 NSW 2145 Westmead	13 11 26	
New Zealand	New Zealand National Poison Centre Dunedin School of Medicine, University of Otago	PO Box 56 Dunedin 9054	0800 764 766 (0800 POISON)	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Specific target organ toxicity — Repeated exposure, Category 1 H372
Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS02

GHS08

Signal word (CLP) : Danger

Contains : STODDARD SOLVENT

Hazard statements (CLP) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H372 - Causes damage to organs through prolonged or repeated exposure.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, open flames, sparks. — No smoking.

P211 - Do not spray on an open flame or other ignition source.
P251 - Pressurized container: Do not pierce or burn, even after use.

P261 - Avoid breathing spray, vapours.

P271 - Use only outdoors or in a well-ventilated area.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation. EUH066 - Repeated exposure may cause skin dryness or cracking.

EUH-statements : EUH066 - Repeated exposure may cause

Child-resistant fastening : Applicable Tactile warning : Applicable

2.3. Other hazards

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
MEK (METHYL ETHYL KETONE), BUTANONE	CAS-No.: 78-93-3 EC-No.: 201-159-0	10 – 30	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).]	CAS-No.: 64742-95-6 EC-No.: 265-199-0 EC Index-No.: 649-356-00-4 REACH-no: 01-2119486773- 24	10 – 30	Asp. Tox. 1, H304
HYDROCARBONS, C10-C12, ISOALKANES, <2% AROMATICS	CAS-No.: 90622-57-4 EC-No.: 923-037-2	10 – 30	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
STODDARD SOLVENT	CAS-No.: 8052-41-3 EC-No.: 232-489-3	10 – 30	Flam. Liq. 3, H226 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Solvent naphtha (petroleum), light aliph.	CAS-No.: 64742-89-8 EC-No.: 265-192-2	5 – 10	Asp. Tox. 1, H304
Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclics, <2% aromatics	CAS-No.: 64742-47-8 EC-No.: 265-149-8 REACH-no: 01-2119456620- 43	1 – 3	Flam. Liq. 3, H226 Asp. Tox. 1, H304
Xylene substance with a Community workplace exposure limit	CAS-No.: 1330-20-7 EC-No.: 215-535-7 EC Index-No.: 601-022-00-9 REACH-no: 01-2119488216- 32	1 – 3	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Asp. Tox. 1, H304 STOT SE 3, H335 Eye Irrit. 2, H319 Aquatic Chronic 3, H412
Isobutyl methacrylate	CAS-No.: 97-86-9 EC-No.: 202-613-0	1 – 3	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335
Toluene	CAS-No.: 108-88-3 EC-No.: 203-625-9	0.1 – 1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical

advice (show the label where possible).

First-aid measures after inhalation : Cough. Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Repeated exposure may cause skin dryness or cracking.

10/11/2021 (Revision date) GB - en 3/15

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Direct contact with the eyes is likely to be

irritating. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation

persists: Get medical advice/attention.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Causes damage to organs through prolonged or repeated exposure.

Symptoms/effects after inhalation : Shortness of breath.

Symptoms/effects after eye contact : Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of

burns and injuries.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire fighting water from entering the environment. DO NOT fight fire

when fire reaches explosives. Evacuate area.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : No open flames. No smoking. Isolate from fire, if possible, without unnecessary risk.

Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible.

Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

10/11/2021 (Revision date) GB - en 4/15

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: Hazardous waste due to potential risk of explosion. Do not pierce or burn, even after use.

Precautions for safe handling

: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vaneur. Do not spray on an energiage or other invition source. Do not breather

formation of vapour. Do not spray on an open flame or other ignition source. Do not breathe

dust/fume/gas/mist/vapours/spray.

: Wash hands, forearms and face thoroughly after handling. Do not eat, drink or smoke when

using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

Hygiene measures

: Proper grounding procedures to avoid static electricity should be followed.

Storage conditions

: Keep only in the original container in a cool, well ventilated place away from : Keep $\,$

container closed when not in use. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Keep in fireproof place.

Incompatible products Incompatible materials

: Strong bases. Strong acids.

: Sources of ignition. Direct sunlight. Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Xylene (1330-20-7)				
EU - Indicative Occupational Exposure Limit (IOEL)				
Local name	Xylene, mixed isomers, pure			
IOEL TWA [ppm]	50 ppm			
IOEL STEL	442 mg/m³			
IOEL STEL [ppm]	100 ppm			
Remark	Skin			
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC			
France - Occupational Exposure Limits				
Local name	Xylène: mélange d'isomères			
VME (OEL TWA)	221 mg/m³			
VME (OEL TWA) [ppm]	50 ppm			
VLE (OEL C/STEL)	442 mg/m³			
VLE (OEL C/STEL) [ppm]	100 ppm			
Remark	Valeurs règlementaires contraignantes; risque de pénétration percutanée			
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487)			
Germany - Occupational Exposure Limits (TRGS 90	0)			
Local name	Xylol (alle Isomeren)			
AGW (OEL TWA) [1]	220 mg/m³			
AGW (OEL TWA) [2]	50 ppm			
Peak exposure limitation factor	2(II)			

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Xylene (1330-20-7)				
Remark	DFG;EU;H			
Regulatory reference	TRGS900			
Germany - Biological limit values (TRGS 903)				
Local name	Xylol (alle Isomere)			
Biological limit value	2000 mg/l Parameter: Methylhippur-(Tolur-) säure (alle Isomere) - Untersuchungsmaterial: U = Urin - Probenahmezeitpunkt: b) Expositionsende, bzw. Schichtende - Festlegung/Begründung: 11/2016 DFG			
Regulatory reference	TRGS 903			
United Kingdom / Australia / New Zealand - Occupa	tional Exposure Limits			
Local name	Xylene			
WEL TWA (OEL TWA) [1]	220 mg/m³ o-,m-,p- or mixed isomers			
WEL TWA (OEL TWA) [2]	50 ppm o-,m-,p- or mixed isomers			
WEL STEL (OEL STEL)	441 mg/m³ o-,m-,p- or mixed isomers			
WEL STEL (OEL STEL) [ppm]	100 ppm o-,m-,p- or mixed isomers			
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)			
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE			
United Kingdom / Australia / New Zealand - Biological limit values				
Local name	Xylene, o-, m-, p- or mixed isomers			
BMGV	650 mmol/mol Creatinine Parameter: methyl hippuric acid - Medium: urine - Sampling time: Post shift			
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE			

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses

8.2.2.2. Skin protection

Hand protection:

Wear protective gloves.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

8.2.2.3. Respiratory protection

Respiratory protection:

Wear appropriate mask

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Other information:

Explosive limits

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour : Colourless. Appearance : Liquid. Odour : characteristic. Odour threshold : Not available Melting point : Not available Freezing point : Not available Boiling point : Not available

Flammability : Non flammable, Extremely flammable aerosol.

: Not available

: Not applicable

Not applicable

Not applicable

: Not available Lower explosive limit (LEL) Upper explosive limit (UEL) : Not available : 41 °C Flash point Auto-ignition temperature : > 250 °C Decomposition temperature : Not available : Not available Viscosity, kinematic : ≈ 134000000 mm²/s Solubility : Not available Partition coefficient n-octanol/water (Log Kow) : Not available Vapour pressure : Not available Vapour pressure at 50 °C : Not available Density : Not available Relative density : Not available Relative vapour density at 20 °C : Not available : Not applicable Particle size Particle size distribution : Not applicable : Not applicable Particle shape Particle aspect ratio : Not applicable : Not applicable Particle aggregation state

9.2. Other information

Particle dustiness

Particle agglomeration state

Particle specific surface area

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 102.3145385075445607209482795

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

10.2. Chemical stability

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

(275°F to 410°F).] (64742-95-6)

LD50 oral rat

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Acute toxicity (definal) Acute toxicity (inhalation)	: Not classified			
Toluene (108-88-3)				
LD50 oral rat	5580 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EU Method B.1 (Acute Toxicity (Oral)), 95% CL: 5300 - 5910			
LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit, Animal sex: male, 95% CL: 9,63 - 20,77			
Isobutyl methacrylate (97-86-9)				
LD50 oral rat	9590 mg/kg bodyweight Animal: rat, Guideline: other:"Appraisal of the safety of chemicals in foods, drugs and cosmetics," by the Staff of the Division of Pharmacology, FDA, (1959)			
Xylene (1330-20-7)				
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male			
Solvent naphtha (petroleum), light aliph. (64742-89-8)				
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)			
Hydrocarbons, C11-14, n-alkanes, isoalkane	es, cyclics, <2% aromatics (64742-47-8)			
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.1175 (Acute Oral Toxicity), Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)			
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)			
LC50 Inhalation - Rat	> 5.28 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), 95% CL: 0,42 -			
hydrocarbons obtained from distillation of a	by boiling point naphtha -unspecified; [A complex combination of aromatic streams. It consists predominantly of aromatic hydrocarbons having of C8 through C10 and boiling in the range of approximately 135°C to 210°C			

Toxicity)
Skin corrosion/irritation : Not classified

> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral

Safety Data Sheet

according to Regulation (E	:C) NIA	1007/2006 (D	with its amondment	Dogulation	/EII	2020/272
according to regulation (L	.U/ NU.	1301/2000 (1	with its amendment	Negulation	(LU	1 2020/010

	a	
Additional information :	Repeated exposure may cause skin dryness or cracking.	
Serious eye damage/irritation :	Not classified	
Respiratory or skin sensitisation :	Not classified	
Additional information :	Based on available data, the classification criteria are not met	
Germ cell mutagenicity :	Not classified	
Additional information :	Based on available data, the classification criteria are not met	
Carcinogenicity : Additional information :	Not classified Based on available data, the classification criteria are not met	
Reproductive toxicity :	Not classified	
Additional information :	Based on available data, the classification criteria are not met	
Hydrocarbons, C11-14, n-alkanes, isoalkanes,		
NOAEL (animal/male, F0/P)	≥ 3000 mg/kg bodyweight Animal: rat, Animal sex: male	
STOT-single exposure :	Not classified	
Additional information : Isobutyl methacrylate (97-86-9)	Based on available data, the classification criteria are not met	
STOT-single exposure	May cause respiratory irritation.	
	indy saude respiratory initiation.	
Xylene (1330-20-7) STOT-single exposure	May cause respiratory irritation	
<u> </u>	May cause respiratory irritation.	
MEK (METHYL ETHYL KETONE), BUTANONE		
STOT-single exposure	May cause drowsiness or dizziness.	
STOT-repeated exposure :	Causes damage to organs through prolonged or repeated exposure.	
Toluene (108-88-3)		
LOAEL (oral, rat, 90 days)	1250 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
NOAEL (oral, rat, 90 days)	625 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxic Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
NOAEC (inhalation, rat, vapour, 90 days)	2.355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90-Day Study)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.	
Isobutyl methacrylate (97-86-9)		
LOAEC (inhalation, rat, gas, 90 days)	952 ppm Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28- Day Study)	
NOAEL (oral, rat, 90 days)	120 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity in Rodents)	
Xylene (1330-20-7)		
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)	
Hydrocarbons, C11-14, n-alkanes, isoalkanes,	, cyclics, <2% aromatics (64742-47-8)	
NOAEL (oral, rat, 90 days)	750 mg/kg bodyweight Animal: rat, Animal sex: female	
NOAEC (inhalation, rat, vapour, 90 days)	≥ 0.024 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)	
STODDARD SOLVENT (8052-41-3)		
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.	
Aspiration hazard :	Not classified	
Additional information :	Based on available data, the classification criteria are not met	

10/11/2021 (Revision date) GB - en 9/15

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

WINSOR & NEWTON PROFESSIONAL GLOSS VARNISH SPRAY		
Vaporizer aerosol		
Viscosity, kinematic	cosity, kinematic ≈ 134000000 mm²/s	

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Potential adverse human health effects and symptoms

: Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term : Not classified

(acute)

Hazardous to the aquatic environment, long-term : Harmful to aquatic life with long lasting effects.

(chronic)

,	
Toluene (108-88-3)	
LC50 - Fish [1]	5.5 mg/l Test organisms (species): Oncorhynchus kisutch
LOEC (chronic)	2.76 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.74 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC chronic fish	1.39 mg/l Test organisms (species): Oncorhynchus kisutch Duration: '40 d'
Isobutyl methacrylate (97-86-9)	
LC50 - Fish [1]	20 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 29 mg/l Test organisms (species): Daphnia magna
EC50 96h - Algae [1]	14 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
Xylene (1330-20-7)	
LC50 - Fish [1]	2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'
MEK (METHYL ETHYL KETONE), BUTANONE	(78-93-3)
LC50 - Fish [1]	2993 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	308 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	1972 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	2029 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
	•

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

12.2. Persistence and degradability

WINSOR & NEWTON PROFESSIONAL GLOSS VARNISH SPRAY

Persistence and degradability May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

WINSOR & NEWTON PROFESSIONAL GLOSS VARNISH SPRAY

Bioaccumulative potential Not established.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in

: Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Additional information : Flammable vapours may accumulate in the container.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN			
14.1. UN number or ID number						
UN 1950	UN 1950	UN 1950	UN 1950			
14.2. UN proper shipping name	e					
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS			
Transport document description						
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1			
14.3. Transport hazard class(e	s)					
2.1	2.1	2.1	2.1			
2	2	2	2			

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN		
14.4. Packing group					
Not applicable	Not applicable Not applicable		Not applicable		
14.5. Environmental hazards					
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No		
No supplementary information available					

14.6. Special precautions for user

Overland transport

Classification code (ADR) : 5F

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 11

Excepted quantities (ADR) : E0

Packing instructions (ADR) : P207

Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR):MP9Transport category (ADR):2Special provisions for carriage - Packages (ADR):V14Special provisions for carriage - Loading, unloading:CV9, CV12

and handling (ADR)

Special provisions for carriage - Operation (ADR) : S2 Tunnel restriction code (ADR) : D

Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Packing instructions (IMDG) : P207, LP200
Special packing provisions (IMDG) : PP87, L2
EmS-No. (Fire) : F-D
EmS-No. (Spillage) : S-U
Stowage category (IMDG) : None
Stowage and handling (IMDG) : SW1, SW22
Segregation (IMDG) : SG69

Air transport

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

Inland waterway transport

Classification code (ADN) : 5F

Special provisions (ADN) : 190, 327, 344, 625

Limited quantities (ADN) : 1 L

Excepted quantities (ADN) : E0

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01, VE04

Number of blue cones/lights (ADN) : 1

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

15.1.2. National regulations

France

France				
Occupational diseases				
Code Description	Description			
RG 4 BIS Gastrointestinal disord	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them			
hydrocarbons and mix alcohols; glycols, glyc	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide			
Germany				
Water hazard class (WGK) Hazardous Incident Ordinance (12. BImSchV)	: WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1): Is not subject of the Hazardous Incident Ordinance (12. BImSchV)			
Netherlands				
SZW-lijst van kankerverwekkende stoffen SZW-lijst van mutagene stoffen	: Solvent naphtha (petroleum), light aliph.,Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclics, <2% aromatics,STODDARD SOLVENT,Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).] are listed : Solvent naphtha (petroleum), light aliph.,Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclics, <2% aromatics,STODDARD SOLVENT,Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the			
	range of approximately 135°C to 210°C (275°F to 410°F).] are listed			
SZW-lijst van reprotoxische stoffen – Borstvoeding SZW-lijst van reprotoxische stoffen – Vruchtbaarheid				
SZW-lijst van reprotoxische stoffen – Ontwikkeling	: Toluene,Xylene are listed			
Denmark				
Class for fire hazard	: Class II-1			
Store unit	: 5 liter			
Classification remarks	: R10 <h222;h229;h372;h412>; Emergency management guidelines for the storage of flammable liquids must be followed</h222;h229;h372;h412>			
Danish National Regulations	: Young people below the age of 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with			

Switzerland

Storage class (LK) : LK 2 - Liquefied or pressurized gases

CH - VOC (SR 814.018) : 51.952792055586081 %

10/11/2021 (Revision date) GB - en 13/15

carcinogens must be followed during use and disposal

The requirements from the Danish Working Environment Authorities regarding work with

the product

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

United Kingdom / Australia / New Zealand

Other information

: This SDS is prepared in accordance with the model Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals.

Please read instructions / label before using product.

EMERGENCY CONTACTS

Jasco Pty Ltd : 02 9807 1555

Police and Fire Brigade : 000
Poisons information centre : 13 11 26
Safety Data Sheet applicable regions : Australia

This SDS is prepared in accordance with the model Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals. Supplied as permitted by New Zealand regulations; EPA Hazardous Substances (Safety Data Sheet) notice.

Please read instructions / label before using product.

EMERGENCY CONTACTS

Jasco Pty Ltd : 02 9807 1555

Poisons information centre : 0800 764 766 (0800 POISON)

Safety Data Sheet applicable regions : New Zealand.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE

COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and

amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-statements:		
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4	
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2	
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3	
Asp. Tox. 1	Aspiration hazard, Category 1	
EUH066	Repeated exposure may cause skin dryness or cracking.	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Liq. 2	Flammable liquids, Category 2	
Flam. Liq. 3	Flammable liquids, Category 3	
H222	Extremely flammable aerosol.	
H225	Highly flammable liquid and vapour.	
H226	Flammable liquid and vapour.	
H229	Pressurised container: May burst if heated.	
H304	May be fatal if swallowed and enters airways.	
H312	Harmful in contact with skin.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	

10/11/2021 (Revision date) GB - en 14/15

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Full text of H- and EUH-statements:		
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H335	May cause respiratory irritation.	
H336	May cause drowsiness or dizziness.	
H361	Suspected of damaging fertility or the unborn child.	
H372	Causes damage to organs through prolonged or repeated exposure.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
Repr. 2	Reproductive toxicity, Category 2	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
Skin Sens. 1	Skin sensitisation, Category 1	
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1	
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2	
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:				
Aerosol 1	H222;H229	Expert judgment		
STOT RE 1	H372	Expert judgment		
Aquatic Chronic 3	H412	Expert judgment		

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.