



Trade name: Marabu Porc&Glas Painter 070, 0,8mm

Version: 10 / GB

Date revised: 15.11.2023

Substance number: 01230011070

Replaces Version: 9 / GB

Print date: 15.11.23

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Marabu Porc&Glas Painter 070, 0,8mm

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/preparation

Paint

1.3. Details of the supplier of the safety data sheet

Address/Manufacturer

Marabu GmbH & Co. KG
Asperger Strasse 4
71732 Tamm
Germany
Telephone no. +49-7141/691-0
Information provided by / telephone Department product safety
E-mail address of person responsible PRSI@marabu.com
for this SDS

1.4. Emergency telephone number

(+49) (0)621-60-43333

SECTION 2: Hazards identification ***

2.1. Classification of the substance or mixture

This product is not classified hazardous in accordance with Regulation (EC) No 1272/2008.

2.2. Label elements

Labelling according to regulation (EC) No 1272/2008

EUH208 Contains 2-Methyl-2H-isothiazol-3-one, 1,2-Benzisothiazol-3(2h)-one, May produce an allergic reaction.

Supplemental information

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3. Other hazards

No special hazards have to be mentioned.

*
*
*

The product contains no PBT substances. The product contains no vPvB substances. This product does not contain a substance that has endocrine disrupting properties with respect to human. The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients

Pyridin-2-thiol-1-oxide, sodium salt

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Marabu Porc&Glas Painter 070, 0,8mm

Version: 10 / GB

Date revised: 15.11.2023

Substance number: 01230011070

Replaces Version: 9 / GB

Print date: 15.11.23

CAS No. 3811-73-2
 EINECS no. 223-296-5
 Concentration \geq 0,001 < 0,1 %
 Classification (Regulation (EC) No. 1272/2008)
 Eye Irrit. 2 H319
 Acute Tox. 4 H302
 Acute Tox. 3 H331
 Aquatic Acute 1 H400
 Aquatic Chronic 2 H411
 Acute Tox. 3 H311
 STOT RE 1 H372 Nervous system
 Skin Irrit. 2 H315
 Skin Sens. 1 H317

Concentration limits (Regulation (EC) No. 1272/2008)
 Aquatic Acute 1 H400 M = 100

Bronopol (INN)

CAS No. 52-51-7
 EINECS no. 200-143-0
 Registration no. 01-2119980938-15
 Concentration \geq 0,01 < 0,1 %
 Classification (Regulation (EC) No. 1272/2008)
 Eye Dam. 1 H318
 Skin Irrit. 2 H315
 STOT SE 3 H335
 Acute Tox. 4 H302
 Acute Tox. 4 H312
 Aquatic Acute 1 H400
 Aquatic Chronic 1 H410

Concentration limits (Regulation (EC) No. 1272/2008)
 Aquatic Acute 1 H400 M = 10
 Aquatic Chronic 1 H410 M = 1

1,2-Benzisothiazol-3(2h)-one

CAS No. 2634-33-5
 EINECS no. 220-120-9
 Concentration < 0,05 %
 Classification (Regulation (EC) No. 1272/2008)
 Aquatic Acute 1 H400
 Skin Sens. 1 H317
 Acute Tox. 4 H302
 Skin Irrit. 2 H315
 Eye Dam. 1 H318
 Acute Tox. 2 H330
 Aquatic Chronic 2 H411

Concentration limits (Regulation (EC) No. 1272/2008)
 Skin Sens. 1 H317 \geq 0,05

2-Methyl-2H-isothiazol-3-one

CAS No. 2682-20-4
 EINECS no. 220-239-6
 Concentration < 0,0015 %
 Classification (Regulation (EC) No. 1272/2008)
 Acute Tox. 3 H301
 Acute Tox. 2 H330
 Skin Corr. 1B H314



Trade name: Marabu Porc&Glas Painter 070, 0,8mm

Version: 10 / GB

Date revised: 15.11.2023

Substance number: 01230011070

Replaces Version: 9 / GB

Print date: 15.11.23

Eye Dam. 1	H318
Aquatic Acute 1	H400
Skin Sens. 1A	H317
Aquatic Chronic 1	H410
Acute Tox. 3	H311

Concentration limits (Regulation (EC) No. 1272/2008)

Skin Sens. 1A	H317	>= 0,0015
Aquatic Acute 1	H400	M = 10

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

Adhere to personal protective measures when giving first aid

Use personal protective equipment in case of possible contact with the product (see section 8).

4.2. Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11. Further symptoms are possible.

4.3. Indication of any immediate medical attention and special treatment needed

Hints for the physician / treatment

Treat symptomatically

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol resistant foam, CO₂, powders, water spray/mist

Non suitable extinguishing media

water jet

5.2. Special hazards arising from the substance or mixture

In the event of fire the following can be released: Carbon monoxide (CO); Carbon dioxide (CO₂); dense black smoke; Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required.

5.3. Advice for firefighters



Trade name: Marabu Porc&Glas Painter 070, 0,8mm

Version: 10 / GB

Date revised: 15.11.2023

Substance number: 01230011070

Replaces Version: 9 / GB

Print date: 15.11.23

Special protective equipment for fire-fighting

Use self-contained breathing apparatus. Wear full chemical protective clothing. Fire fighter's clothing must conform to European standard EN469.

Other information

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: Remove persons to safety. Keep away unprotected persons. Avoid contact with skin, eyes and clothing. Avoid breathing vapours. For emergency responders: Wear personal protective equipment. Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Do not allow to enter drains or waterways. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

6.4. Reference to other sections

Information regarding personal protective measures, see Section 8. Information regarding waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid skin and eye contact. Avoid inhalation of vapour and spray mist. Smoking, eating and drinking shall be prohibited in application area. For personal protection see Section 8. Never use pressure to empty: container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or water courses.

Advice on protection against fire and explosion

No special measures required.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in accordance with national regulation

Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

Further information on storage conditions

Observe label precautions. Store between 15 and 30 °C in a dry, well ventilated place away from sources of heat and direct sunlight. Protect from frost. If the storage conditions are not observed, the minimum shelf life is no longer guaranteed. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

7.3. Specific end use(s)

Paint

SECTION 8: Exposure controls/personal protection ***



Trade name: Marabu Porc&Glas Painter 070, 0,8mm

Version: 10 / GB

Date revised: 15.11.2023

Substance number: 01230011070

Replaces Version: 9 / GB

Print date: 15.11.23

8.1. Control parameters

Other information

There are not known any further control parameters.

Derived No/Minimal Effect Levels (DNEL/DMEL) ***

Bronopol (INN)

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	3,5	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	10,5	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	2,5	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	2,5	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	2	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Short term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	6	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Local effects	
Concentration	8	µg/cm ²
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Marabu Porc&Glas Painter 070, 0,8mm

Version: 10 / GB

Date revised: 15.11.2023

Substance number: 01230011070

Replaces Version: 9 / GB

Print date: 15.11.23

Duration of exposure	Short term	
Route of exposure	dermal	
Mode of action	Local effects	
Concentration	8	µg/cm ²
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	0,6	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	1,8	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	0,6	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	0,6	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	0,7	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	2,1	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Local effects	
Concentration	4	µg/cm ²
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short term	
Route of exposure	dermal	

Safety data sheet in accordance with regulation (EC) No 1907/2006



Trade name: Marabu Porc&Glas Painter 070, 0,8mm

Version: 10 / GB

Date revised: 15.11.2023

Substance number: 01230011070

Replaces Version: 9 / GB

Print date: 15.11.23

Mode of action Local effects
Concentration 4 µg/cm²

Type of value Derived No Effect Level (DNEL)
Reference group Consumer
Duration of exposure Long term
Route of exposure oral

Mode of action Systemic effects
Concentration 0,18 mg/kg/d

Type of value Derived No Effect Level (DNEL)
Reference group Consumer
Duration of exposure Short term

Route of exposure oral
Mode of action Systemic effects
Concentration 0,5 mg/kg/d

1,2-Benzisothiazol-3(2h)-one

Type of value Derived No Effect Level (DNEL)
Reference group Consumer
Duration of exposure Long term

Route of exposure inhalative
Mode of action Systemic effects
Concentration 1,2 mg/m³

Type of value Derived No Effect Level (DNEL)
Reference group Worker
Duration of exposure Long term

Route of exposure inhalative
Mode of action Systemic effects
Concentration 6,81 mg/m³

Type of value Derived No Effect Level (DNEL)
Reference group Worker
Duration of exposure Long term

Route of exposure dermal
Mode of action Systemic effects
Concentration 96,9 mg/kg/d

Type of value Derived No Effect Level (DNEL)
Reference group Consumer
Duration of exposure Long term

Route of exposure dermal
Mode of action Systemic effects
Concentration 0,345 mg/kg/d

Predicted No Effect Concentration (PNEC) ***

Bronopol (INN)

Type of value PNEC
Type Freshwater
Concentration 0,01 mg/l

Type of value PNEC
Type Saltwater
Concentration 0,001 mg/l

Type of value PNEC



Trade name: Marabu Porc&Glas Painter 070, 0,8mm

Version: 10 / GB

Date revised: 15.11.2023

Substance number: 01230011070

Replaces Version: 9 / GB

Print date: 15.11.23

Type	Water (intermittent release)	
Concentration	0,003	mg/l
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	0,43	mg/l
Type of value	PNEC	
Type	Freshwater sediment	
Concentration	0,041	mg/kg
Type of value	PNEC	
Type	Marine sediment	
Concentration	0,003	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	0,5	mg/kg
1,2-Benzisothiazol-3(2h)-one		
Type of value	PNEC	
Type	Freshwater	
Concentration	0,004	mg/l
Type of value	PNEC	
Type	Water (intermittent release)	
Concentration	0,0011	mg/l
Type of value	PNEC	
Type	Saltwater	
Concentration	0,0004	mg/l
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	1,03	mg/l
Type of value	PNEC	
Type	Freshwater sediment	
Concentration	0,0499	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	3,0	mg/kg
Type of value	PNEC	
Type	Marine sediment	
Concentration	0,00499	mg/kg

8.2. Exposure controls

Exposure controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

General protective and hygiene measures

Observe the usual precautions for handling chemicals. Wash hands and / or face before breaks and after work. Take off dirty, soaked clothes immediately. Wash soiled clothing before re-use.



Trade name: Marabu Porc&Glas Painter 070, 0,8mm

Version: 10 / GB

Date revised: 15.11.2023

Substance number: 01230011070

Replaces Version: 9 / GB

Print date: 15.11.23

Respiratory protection

If workers could be exposed to concentrations above the exposure limit they should use a respirator to EN 140, fitted with a filter suitable for both particulates and vapours, to EN 14387, with an assigned protection factor of at least 10 (e.g. A2P3) . Selection of any respiratory protective equipment should ensure that it is adequate to reduce exposure to protect the worker's health and is suitable for the wearer, task and environment, including consideration of the facial features of the wearer.

Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

Use gloves tested according to EN 374.

For prolonged or repeated handling, use

Appropriate Material	vinyl		
Material thickness	0,1	mm	
Breakthrough time	> 480	min	

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

Eye protection

Use safety eyewear tested according to EN ISO 16321-1 designed to protect against splash of liquids.

Body protection

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre. Cotton or cotton/synthetic overalls or coveralls are normally suitable.

Environmental exposure controls

Do not allow to enter drains or water courses.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	liquid
Colour	white
Odour	slightly perceptible
Melting point	
Remarks	Not applicable due to nature of the product
Freezing point	
Remarks	Not applicable due to nature of the product
Boiling point or initial boiling point and boiling range	
Reference substance	Water
Value	appr. 100 °C
Pressure	1.013 hPa
Source	Literature value
Flammability	
Not ignitable	
Upper and lower explosive limits	
Remarks	not determined
Flash point	



Trade name: Marabu Porc&Glas Painter 070, 0,8mm

Version: 10 / GB

Date revised: 15.11.2023

Substance number: 01230011070

Replaces Version: 9 / GB

Print date: 15.11.23

Remarks Not applicable due to nature of the product

Auto-ignition temperature

Remarks not determined

Decomposition temperature

Remarks No decomposition if used as prescribed.

pH value

Value 8 to 9
 Temperature 20 °C
 Method WTW PH 340

Viscosity**kinematic**

Value appr. 4 to 55 mm²/s
 Temperature 20 °C
 Method derived from dynamic viscosity

Solubility(ies)

Remarks miscible with water

Partition coefficient n-octanol/water (log value)

Remarks Not applicable due to nature of the product

Vapour pressure

Value appr. 23 hPa
 Temperature 20 °C
 Method Value taken from the literature

Density and/or relative density

Value 1,04 g/cm³
 Temperature 20 °C
 Method DIN EN ISO 2811

Relative vapour density

Value > 1

Particle characteristics

Remarks Not applicable due to nature of the product

9.2. Other information**Other information**

None known

SECTION 10: Stability and reactivity**10.1. Reactivity**

None

10.2. Chemical stability

Stable under recommended storage and handling conditions (see section 7).

10.3. Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.4. Conditions to avoid

Protect from heat/overheating. When exposed to high temperatures may produce hazardous decomposition products.

10.5. Incompatible materials

Oxidising agents, strongly alkaline substances, Strongly acidic substances



Trade name: Marabu Porc&Glas Painter 070, 0,8mm

Version: 10 / GB

Date revised: 15.11.2023

Substance number: 01230011070

Replaces Version: 9 / GB

Print date: 15.11.23

10.6. Hazardous decomposition products

See chapter 5.2 (Firefighting measures - Special hazards arising from the substance or mixture). No decomposition during or intended use (see section 1).

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute oral toxicity**

Remarks Based on available data, the classification criteria are not met.

Acute oral toxicity (Components)**1,2-Benzisothiazol-3(2h)-one**

Species	rat		
LD50		490	mg/kg

Pyridin-2-thiol-1-oxide, sodium salt

ATE		500	mg/kg
-----	--	-----	-------

Acute dermal toxicity

Remarks Based on available data, the classification criteria are not met.

Acute dermal toxicity (Components)**1,2-Benzisothiazol-3(2h)-one**

Species	rat		
LD50		4115	mg/kg

Pyridin-2-thiol-1-oxide, sodium salt

ATE		790	mg/kg
-----	--	-----	-------

Acute inhalational toxicity

Remarks Based on available data, the classification criteria are not met.

Acute inhalative toxicity (Components)**Pyridin-2-thiol-1-oxide, sodium salt**

ATE		0,5	mg/l
Administration/Form	Dust/Mist		

Skin corrosion/irritation

Remarks Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Remarks Based on available data, the classification criteria are not met.

Sensitization

Remarks Based on available data, the classification criteria are not met.

Mutagenicity

Remarks Based on available data, the classification criteria are not met.

Reproductive toxicity

Remarks Based on available data, the classification criteria are not met.

Carcinogenicity

Remarks Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity (STOT)**Single exposure**

Remarks Based on available data, the classification criteria are not met.

Repeated exposure

Remarks Based on available data, the classification criteria are not met.

Aspiration hazard



Trade name: Marabu Porc&Glas Painter 070, 0,8mm

Version: 10 / GB

Date revised: 15.11.2023

Substance number: 01230011070

Replaces Version: 9 / GB

Print date: 15.11.23

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties with respect to humans

The product does not contain a substance that has endocrine disrupting properties with respect to humans.

Other information

There are no data available on the mixture itself.

The mixture has been assessed following the additivity method of the CLP Regulation (EC) No 1272/2008 and classified for toxicological hazards accordingly.

SECTION 12: Ecological information

12.1. Toxicity

General information

There are no data available on the mixture itself. Do not allow to enter drains or water courses. The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as dangerous for the environment.

Fish toxicity (Components)

Bronopol (INN)

Species	rainbow trout (<i>Oncorhynchus mykiss</i>)		
LC50	3		mg/l
Duration of exposure	96	h	
Method	OECD 203		

Bronopol (INN)

Species	rainbow trout (<i>Oncorhynchus mykiss</i>)		
NOEC	2,61		mg/l
Duration of exposure	28	d	
Method	OECD 203		

1,2-Benzisothiazol-3(2h)-one

Species	rainbow trout (<i>Oncorhynchus mykiss</i>)		
LC50	2,18		mg/l
Duration of exposure	96	h	

Daphnia toxicity (Components)

Bronopol (INN)

Species	Daphnia magna		
EC50	1,04		mg/l
Duration of exposure	48	h	
Method	OECD 202		

Bronopol (INN)

Species	Daphnia magna		
NOEC	0,06		mg/l
Duration of exposure	21	d	
Method	OECD 211		

1,2-Benzisothiazol-3(2h)-one

Species	Daphnia magna		
EC50	2,94		mg/l
Duration of exposure	48	h	

Algae toxicity (Components)

Bronopol (INN)

Species	Pseudokirchneriella subcapitata		
EC50	0,068		mg/l
Duration of exposure	72	h	



Trade name: Marabu Porc&Glas Painter 070, 0,8mm

Version: 10 / GB

Date revised: 15.11.2023

Substance number: 01230011070

Replaces Version: 9 / GB

Print date: 15.11.23

Method	OECD 201	
Bronopol (INN)		
Species	Pseudokirchneriella subcapitata	
NOEC	0,0025	mg/l
Duration of exposure	72	h
Method	OECD 201	
1,2-Benzisothiazol-3(2h)-one		
Species	Pseudokirchneriella subcapitata	
ErC50	0,11	mg/l
Duration of exposure	72	h

12.2. Persistence and degradability

General information

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

General information

There are no data available on the mixture itself.

Partition coefficient n-octanol/water (log value)

Remarks Not applicable due to nature of the product

12.4. Mobility in soil

General information

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

General information

There are no data available on the mixture itself.

Results of PBT and vPvB assessment

The product contains no PBT substances
The product contains no vPvB substances.

12.6 Endocrine disrupting properties

Endocrine disrupting properties with respect to the environment

The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

General information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations for the product

Do not allow to enter drains or water courses.

Wastes and emptied containers should be classified in accordance with relevant national regulation.

The European Waste Catalogue classification of this product, when disposed of as waste is

EWG waste code 08 01 19* aqueous suspensions containing paint or varnish containing organic solvents or other dangerous substances

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

For further information contact your local waste authority.



Trade name: Marabu Porc&Glas Painter 070, 0,8mm

Version: 10 / GB

Date revised: 15.11.2023

Substance number: 01230011070

Replaces Version: 9 / GB

Print date: 15.11.23

Disposal recommendations for packaging

Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.
 Empty containers must be scrapped or reconditioned.
 Dispose of containers contaminated by the product in accordance with local or national legal provisions.

SECTION 14: Transport information

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
14.1. UN number	The product does not constitute a hazardous substance in land transport.-	The product does not constitute a hazardous substance in sea transport.-	The product does not constitute a hazardous substance in air transport.-
14.2. UN proper shipping name	-	-	-
14.3. Transport hazard class(es)	-	-	-
Subsidiary risk		-	-
Label			
14.4. Packing group	-	-	-
Transport category	0		

Information for all modes of transport

14.6. Special precautions for user

Transport within the user's premises:
 Always transport in closed containers that are upright and secure.
 Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Other information

14.7 Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC

VOC (EU) 0,74 %
 VOC (EU) 7,7 g/l

Other regulations, restrictions and prohibition regulations

The product complies with the requirements of the Persistent Organic Pollutants Regulation 2019/1021.
 The product complies with the requirements of Regulation 1005/2009 on substances that deplete the ozone layer.
 The product is not subject to Regulation 649/2012 on the export and import of dangerous chemicals.

Other information

All components are contained in the DSL inventory.
 All components are contained in the ECL inventory.



Trade name: Marabu Porc&Glas Painter 070, 0,8mm

Version: 10 / GB

Date revised: 15.11.2023

Substance number: 01230011070

Replaces Version: 9 / GB

Print date: 15.11.23

15.2. Chemical safety assessment

For this preparation a chemical safety assessment has not been carried out.

SECTION 16: Other information

Hazard statements listed in Chapter 3

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

CLP categories listed in Chapter 3

Acute Tox. 2	Acute toxicity, Category 2
Acute Tox. 3	Acute toxicity, Category 3
Acute Tox. 4	Acute toxicity, Category 4
Aquatic Acute 1	Hazardous to the aquatic environment, acute, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic, Category 2
Eye Dam. 1	Serious eye damage, Category 1
Eye Irrit. 2	Eye irritation, Category 2
Skin Corr. 1B	Skin corrosion, Category 1B
Skin Irrit. 2	Skin irritation, Category 2
Skin Sens. 1	Skin sensitization, Category 1
Skin Sens. 1A	Skin sensitization, Category 1A
STOT RE 1	Specific target organ toxicity - repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity - single exposure, Category 3

Supplemental information

Relevant changes compared with the previous version of the safety data sheet are marked with: ***
 This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.
 The information in this Safety Data Sheet is based on the present state of knowledge and current legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.
 The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.